

Revision: 28.07.2021 Printing date 28.07.2021

Hazardous according to criteria of Australian Safety and Compensation Council.

1 Identification

- · Product identifier
- · Trade name: CALIBRATION MIX- LC/MS ESI (-) ION MIX
- · Article number: MZ301199
- · Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Laboratory chemicals
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

PerkinElmer, Inc. 710 Bridgeport Avenue Shelton, Connecticut 06484 USA CustomerCareUS@perkinelmer.com 203-925-4600

Supplier/Local:

PerkinElmer Australia

Lvl 2, Bldg 5, Brandon Office Park

530-540 Springvale Road

Glen Waverley

Melbourne

VIC 3150

Australia

1-800-033-391

ausales@perkinelmer.com

· Emergency telephone number:

CHEMTREC (within US) 800-424-9300

CHEMTREC (from outside US) +1 703-527-3887 (call collect)


CHEMTREC (within AU) +(61)-290372994

2 Hazard(s) Identification

· Classification of the substance or mixture



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Acute Tox. 3 H331 Toxic if inhaled.

(Contd. on page 2)



Printing date 28.07.2021 Revision: 28.07.2021

Trade name: CALIBRATION MIX- LC/MS ESI (-) ION MIX

(Contd. of page 1)



STOT SE 2 H371 May cause damage to organs.



Acute Tox. 4 H312 Harmful in contact with skin. Eve Irrit. 2A H319 Causes serious eve irritation.

- · Label elements
- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms GHS02, GHS06, GHS08
- · Signal word Danger
- · Hazard-determining components of labelling:

acetonitrile

methanol

· Hazard statements

H225 Highly flammable liquid and vapour.

H312 Harmful in contact with skin.

H331 Toxic if inhaled.

H319 Causes serious eye irritation.

H371 May cause damage to organs.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P241 *Use explosion-proof electrical/ventilating/lighting equipment.*

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Other hazards

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)



Printing date 28.07.2021 Revision: 28.07.2021

Trade name: CALIBRATION MIX- LC/MS ESI (-) ION MIX

		(Contd. of page
Dangerous d	components:	
75-05-8 ace	tonitrile	77.84019
(Flam. Liq. 2, H225 Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Eye Irrit. 2, H319	
67-56-1 met	thanol	9.901%
③	Flam. Liq. 2, H225 Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 STOT SE 1, H370	
Additional C	Components	
7732-18-5	Water	12.0%
7732-18-5	Water SpectraSynQ 2721	
		0.188%
540-69-2	SpectraSynQ 2721	0.188% 0.0339%
540-69-2 99-76-3	SpectraSynQ 2721 2 ammonium formate	0.188% 0.0339% 0.025%
540-69-2 99-76-3	SpectraSynQ 2721 2 ammonium formate 3 methyl 4-hydroxybenzoate	12.0% 0.188% 0.0339% 0.025% 0.011%
540-69-2 99-76-3 393-11-3	SpectraSynQ 2721 ammonium formate methyl 4-hydroxybenzoate 4-Nitro-3-(trifluoro-methyl) aniline Acute Tox. 3, H301; Acute Tox. 3, H311	0.188% 0.0339% 0.025%

4 First Aid Measures

- Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove breathing equipment only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 4)



Printing date 28.07.2021 Revision: 28.07.2021

Trade name: CALIBRATION MIX- LC/MS ESI (-) ION MIX

(Contd. of page 3)

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 5)



Printing date 28.07.2021 Revision: 28.07.2021

Trade name: CALIBRATION MIX- LC/MS ESI (-) ION MIX

(Contd. of page 4)

· Control parameters

· Ingredients with limit values that require monitoring at the workplace:

75-05-8 acetonitrile

WES Short-term value: 101 mg/m³, 60 ppm Long-term value: 67 mg/m³, 40 ppm

67-56-1 methanol

WES Short-term value: 328 mg/m³, 250 ppm Long-term value: 262 mg/m³, 200 ppm Sk

· Additional information: The lists valid during the making were used as basis.

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

ΑU



Printing date 28.07.2021 Revision: 28.07.2021

Trade name: CALIBRATION MIX- LC/MS ESI (-) ION MIX

(Contd. of page 5)

Information on basic physical and chen	nical properties
General Information	
Appearance:	
Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	:: 100 °C
Flash point:	5 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	455 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vape mixtures are possible.
Explosion limits:	
Lower:	4.4 Vol %
Upper:	16 Vol %
Vapour pressure at 20 °C:	97 hPa
Density at 20 °C:	1 g/cm^3
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Fully miscible.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	9.9 %
Water:	12.0 %
Other information	No further relevant information available.



Printing date 28.07.2021 Revision: 28.07.2021

Trade name: CALIBRATION MIX- LC/MS ESI (-) ION MIX

(Contd. of page 6)

10 Stability and Reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity

· LD/LC5	LD/LC50 values relevant for classification:				
75-05-8	75-05-8 acetonitrile				
		2730 mg/kg (rat)			
Dermal LD50 1250 mg/kg (rabbit)		1250 mg/kg (rabbit)			
67-56-1 methanol					
Oral	LD50	5628 mg/kg (rat)			
Dermal	LD50	15800 mg/kg (rabbit)			

- · Primary irritant effect:
- · Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation Irritating effect.
- Respiratory or skin sensitisation No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Toxic

Harmful

Irritant

12 Ecological Information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Not hazardous for water.
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 8)



Printing date 28.07.2021 Revision: 28.07.2021

Trade name: CALIBRATION MIX- LC/MS ESI (-) ION MIX

(Contd. of page 7)

· Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

UN-Number ADG, IMDG, IATA	UN1992
UN proper shipping name	0111992
ADG	1992 FLAMMABLE LIQUID, TOXIC, N.O. (ACETONITRILE, METHANOL)
IMDG, IATA	FLAMMABLE LIQUID, TOXIC, N.O.S. (ACETONITRIL METHANOL)
Transport hazard class(es)	
ADG	
Class	3 (FT1) Flammable liquids.
Label IMDG	3+6.1
Class	3 Flammable liquids.
Label	3/6.1
IATA OF THE PROPERTY OF THE PR	
Class	3 Flammable liquids.
Label	3 (6.1)

(Contd. on page 9)



Printing date 28.07.2021 Revision: 28.07.2021

Trade name: CALIBRATION MIX- LC/MS ESI (-) ION MIX

	(Contd. of page
Packing group	
ADG, IMDG, IATA	II
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	336
EMS Number:	F- E , S - D
Stowage Category	B
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex II of Mar	pol
and the IBC Code	Not applicable.
Transport/Additional information:	
ADG	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1992 FLAMMABLE LIQUID, TOXIC, N.O.
3	(ACETONITRILE, METHANOL), 3 (6.1), II

Safety, hed	alth and environmental regulations/legislation specific for the substance or mixture	
75-05-8	acetonitrile Flam. Liq. 2, H225 Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Eye Irrit. 2, H319	77.8401%
7732-18-5	Water	12.0%
67-56-1	methanol	9.901%

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.

(Contd. on page 10)



Printing date 28.07.2021 Revision: 28.07.2021

Trade name: CALIBRATION MIX- LC/MS ESI (-) ION MIX

(Contd. of page 9)

· Seveso category

H2 ACUTE TOXIC

P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · National regulations:
- · Information about limitation of use:

Workers are not allowed to be exposed to this hazardous material. Exceptions can be made by the authorities in certain cases.

- · Waterhazard class: Generally not hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Disclaimer

The information provided in this Material Safety Data Sheet is based on our present knowledge, and believed to be correct at the date of publication. However, no representation is made concerning its accuracy and completeness. It is intended as guidance only, and is not to be considered a warranty or quality specification. All materials may present unknown hazards, and should be used with caution. Although certain hazards are described, we cannot guarantee that these are the only hazards which exist. PerkinElmer Life and Analytical Sciences shall not be held liable for any damage resulting from handling or from contact with the product.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H370 Causes damage to organs.

· Department issuing SDS: Environmental, Health and Safety

· Contact:

Within the USA: 1-(800)-762-4000 Outside the USA: 1-(203)-712-8488

· Abbreviations and acronyms

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

(Contd. on page 11)



Printing date 28.07.2021 Revision: 28.07.2021

Trade name: CALIBRATION MIX- LC/MS ESI (-) ION MIX

(Contd. of page 10)

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Acute Tox. 3: Acute toxicity – Category 3 Acute Tox 4: Acute toxicity – Category 4

Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
STOT SE 1: Specific target organ toxicity (single exposure) – Category 1
STOT SE 2: Specific target organ toxicity (single exposure) – Category 2

* * Data compared to the previous version altered.

AII.