

acc. to OSHA HCS

Printing date 05/13/2021

Review date 05/13/2021

1 Identification

- **Product identifier**
- **Trade name:** WAV CALIBRATION P-2 TEST MIX
- **Article number** N0582152
- **Application of the substance / the mixture** Laboratory chemicals
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**

PerkinElmer, Inc.
710 Bridgeport Avenue
Shelton, Connecticut 06484 USA
CustomerCareUS@perkinelmer.com
203-925-4600

- **Emergency telephone number:**
CHEMTREC (within US) 800-424-9300
CHEMTREC (from outside US) +1 703-527-3887 (call collect)
CHEMTREC (within AU) +(61)-290372994

2 Hazard(s) identification

- **Classification of the substance or mixture**



Corrosion

Eye Dam. 1 H318 Causes serious eye damage.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms** GHS05
- **Signal word** Danger
- **Hazard-determining components of labeling:**
Hydrochloric Acid
- **Hazard statements**
H318 Causes serious eye damage.
- **Precautionary statements**
P280 Wear eye protection / face protection.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a poison center/doctor.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 3
Fire = 0
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = *3
Fire = 0
Reactivity = 0

(Contd. on page 2)

acc. to OSHA HCS

Printing date 05/13/2021

Review date 05/13/2021

Trade name: WAV CALIBRATION P-2 TEST MIX

(Contd. of page 1)

· **Other hazards**

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **CAS No. Description**



7732-18-5 Water

· **EC number:** 231-791-2














· **Chemical characterization:** Mixtures

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Hazardous components:**

7647-01-0	Hydrochloric Acid	5.0%
	 Skin Corr. 1B, H314; Eye Dam. 1, H318  Acute Tox. 4, H302; STOT SE 3, H335	

· **Additional Components**

7732-18-5	Water	94.9539%
7440-09-7	potassium	0.01%
	 Water-react. 1, H260  Skin Corr. 1B, H314	
7723-14-0	red phosphorus	0.01%
	 Flam. Liq. 2, H225; Flam. Sol. 1, H228 Aquatic Chronic 3, H412	
7783-20-2	ammonium sulphate	0.01%
	 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	
7439-91-0	lanthanum	0.002%
7439-93-2	lithium	0.002%
	 Water-react. 1, H260  Skin Corr. 1B, H314	
7439-96-5	manganese	0.002%
7439-98-7	molybdenum	0.002%
7440-02-0	nickel	0.002%
	 Carc. 2, H351; STOT RE 1, H372  Skin Sens. 1, H317	
7440-20-2	Scandium from Scandium Oxide	0.002%
7440-23-5	sodium	0.002%
	 Water-react. 1, H260  Skin Corr. 1B, H314	
7440-38-2	Arsenic	0.002%
	 Acute Tox. 3, H301; Acute Tox. 3, H331  Carc. 1A, H350  Aquatic Acute 1, H400; Aquatic Chronic 1, H410	

(Contd. on page 3)

acc. to OSHA HCS

Printing date 05/13/2021

Review date 05/13/2021

Trade name: WAV CALIBRATION P-2 TEST MIX

7440-70-2 calcium		(Contd. of page 2)
 Water-react. 2, H261		0.0001%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:		
7647-01-0	Hydrochloric Acid	1.8 ppm
7440-09-7	potassium	2.3 mg/m ³
7723-14-0	red phosphorus	0.27 mg/m ³
7783-20-2	ammonium sulphate	13 mg/m ³
7439-91-0	lanthanum	30 mg/m ³
7439-93-2	lithium	3.3 mg/m ³

(Contd. on page 4)

acc. to OSHA HCS

Printing date 05/13/2021

Review date 05/13/2021

Trade name: WAV CALIBRATION P-2 TEST MIX

(Contd. of page 3)

7439-96-5	manganese	3 mg/m ³
7439-98-7	molybdenum	30 mg/m ³
7440-02-0	nickel	4.5 mg/m ³
7440-20-2	Scandium from Scandium Oxide	30 mg/m ³
7440-23-5	sodium	13 mg/m ³
7440-38-2	Arsenic	1.5 mg/m ³

PAC-2:

7647-01-0	Hydrochloric Acid	22 ppm
7440-09-7	potassium	25 mg/m ³
7723-14-0	red phosphorus	3 mg/m ³
7783-20-2	ammonium sulphate	140 mg/m ³
7439-91-0	lanthanum	330 mg/m ³
7439-93-2	lithium	36 mg/m ³
7439-96-5	manganese	5 mg/m ³
7439-98-7	molybdenum	330 mg/m ³
7440-02-0	nickel	50 mg/m ³
7440-20-2	Scandium from Scandium Oxide	330 mg/m ³
7440-23-5	sodium	140 mg/m ³
7440-38-2	Arsenic	17 mg/m ³

PAC-3:

7647-01-0	Hydrochloric Acid	100 ppm
7440-09-7	potassium	150 mg/m ³
7723-14-0	red phosphorus	18 mg/m ³
7783-20-2	ammonium sulphate	840 mg/m ³
7439-91-0	lanthanum	2,000 mg/m ³
7439-93-2	lithium	220 mg/m ³
7439-96-5	manganese	1,800 mg/m ³
7439-98-7	molybdenum	2,000 mg/m ³
7440-02-0	nickel	99 mg/m ³
7440-20-2	Scandium from Scandium Oxide	2,000 mg/m ³
7440-23-5	sodium	870 mg/m ³
7440-38-2	Arsenic	100 mg/m ³

7 Handling and storage

Handling:

Precautions for safe handling No special precautions are necessary if used correctly.

Information about protection against explosions and fires: No special measures required.

(Contd. on page 5)

acc. to OSHA HCS

Printing date 05/13/2021

Review date 05/13/2021

Trade name: WAV CALIBRATION P-2 TEST MIX

(Contd. of page 4)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

7647-01-0 Hydrochloric Acid

PEL	Ceiling limit value: 7 mg/m ³ , 5 ppm
REL	Ceiling limit value: 7 mg/m ³ , 5 ppm
TLV	Ceiling limit value: 2.98 mg/m ³ , 2 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing.
 - Wash hands before breaks and at the end of work.
 - Avoid contact with the eyes.
 - Avoid contact with the eyes and skin.
- **Breathing equipment:** Not required.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

acc. to OSHA HCS

Printing date 05/13/2021

Review date 05/13/2021

Trade name: WAV CALIBRATION P-2 TEST MIX

· **Eye protection:**

(Contd. of page 5)



Tightly sealed goggles or safety glasses

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Liquid
· Color:	Transparent
· Odor:	Odorless
· Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· Melting point/Melting range:	0 °C (32 °F)
· Boiling point/Boiling range:	100 °C (212 °F)

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not applicable.

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.
Not determined.

· **Explosion limits:**

· Lower:	Not determined.
· Upper:	Not determined.

· **Vapor pressure at 20 °C (68 °F):** 23 hPa (17.3 mm Hg)

· **Density at 20 °C (68 °F):** 1 g/cm³ (8.345 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

· **Water:** Fully miscible.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

· Dynamic:	Not determined.
· Kinematic:	Not determined.

· **Solvent content:**

· **Water:** 95.0 %

(Contd. on page 7)

acc. to OSHA HCS

Printing date 05/13/2021

Review date 05/13/2021

Trade name: WAV CALIBRATION P-2 TEST MIX

(Contd. of page 6)

VOC content:	0.00 %
Solids content:	3.1 %
Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)		
7647-01-0	Hydrochloric Acid	3
7440-02-0	nickel	2B
7440-38-2	Arsenic	1
· NTP (National Toxicology Program)		
7440-02-0	nickel	R
7440-38-2	Arsenic	K
· OSHA-Ca (Occupational Safety & Health Administration)		
7440-38-2	Arsenic	

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

(Contd. on page 8)

acc. to OSHA HCS

Printing date 05/13/2021

Review date 05/13/2021

Trade name: WAV CALIBRATION P-2 TEST MIX



(Contd. of page 7)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Dispose of container and materials in accordance with local, regional and national regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|---|-----------------------------|
| · UN-Number | UN1789 |
| · DOT, ADR, IMDG, IATA | |
| · UN proper shipping name | Hydrochloric acid |
| · DOT | 1789 HYDROCHLORIC ACID |
| · ADR | HYDROCHLORIC ACID, solution |
| · IMDG, IATA | HYDROCHLORIC ACID |
| · Transport hazard class(es) | |
| · DOT | |
|  | |
| · Class | 8 Corrosive substances |
| · Label | 8 |
| · ADR | |
|  | |
| · Class | 8 (C1) Corrosive substances |

(Contd. on page 9)


acc. to OSHA HCS

Printing date 05/13/2021

Review date 05/13/2021



Trade name: WAV CALIBRATION P-2 TEST MIX

(Contd. of page 8)

· Label	8
· IMDG, IATA	
	
· Class	8 Corrosive substances
· Label	8
· Packing group	
· DOT, ADR, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Corrosive substances
· Hazard identification number (Kemler code):	80
· EMS Number:	F-A,S-B
· Segregation groups	Strong acids
· Stowage Category	C
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L
· ADR	
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1789 HYDROCHLORIC ACID, 8, II

*

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture		
7732-18-5	Water	94.9539%
7647-01-0	Hydrochloric Acid	5.0%
	 Skin Corr. 1B, H314; Eye Dam. 1, H318  Acute Tox. 4, H302; STOT SE 3, H335	

(Contd. on page 10)

acc. to OSHA HCS

Printing date 05/13/2021

Review date 05/13/2021

Trade name: WAV CALIBRATION P-2 TEST MIX

		(Contd. of page 9)
7440-09-7	potassium	0.01%
	 Water-react. 1, H260  Skin Corr. 1B, H314	

· **Sara**

· **Section 355 (extremely hazardous substances):**

7647-01-0	Hydrochloric Acid
7723-14-0	red phosphorus

· **Section 313 (Specific toxic chemical listings):**

7647-01-0	Hydrochloric Acid
7723-14-0	red phosphorus
7783-20-2	ammonium sulphate
7439-96-5	manganese
7440-02-0	nickel
7440-38-2	Arsenic

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

7732-18-5	Water	ACTIVE
7647-01-0	Hydrochloric Acid	ACTIVE
7440-09-7	potassium	ACTIVE
7723-14-0	red phosphorus	ACTIVE
7783-20-2	ammonium sulphate	ACTIVE
7439-91-0	lanthanum	ACTIVE
7439-93-2	lithium	ACTIVE
7439-96-5	manganese	ACTIVE
7439-98-7	molybdenum	ACTIVE
7440-02-0	nickel	ACTIVE
7440-20-2	Scandium from Scandium Oxide	ACTIVE
7440-23-5	sodium	ACTIVE
7440-38-2	Arsenic	ACTIVE
7440-70-2	calcium	ACTIVE

· **Hazardous Air Pollutants**

7647-01-0	Hydrochloric Acid
7723-14-0	red phosphorus
7439-96-5	manganese

· **Proposition 65**

· **Chemicals known to cause cancer:**

7440-02-0	nickel
7440-38-2	Arsenic

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

(Contd. on page 11)

acc. to OSHA HCS

Printing date 05/13/2021

Review date 05/13/2021

Trade name: WAV CALIBRATION P-2 TEST MIX

(Contd. of page 10)

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

7723-14-0	red phosphorus	D
7439-96-5	manganese	D
7440-38-2	Arsenic	A

· **TLV (Threshold Limit Value established by ACGIH)**

7647-01-0	Hydrochloric Acid	A4
7439-98-7	molybdenum	A3
7440-02-0	nickel	A5
7440-38-2	Arsenic	A1

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

7440-02-0	nickel
7440-38-2	Arsenic

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to this hazardous material. Exceptions can be made by the authorities in certain cases.

· **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

Disclaimer

The information provided in this Material Safety Data Sheet is based on our present knowledge, and believed to be correct at the date of publication. However, no representation is made concerning its accuracy and completeness. It is intended as guidance only, and is not to be considered a warranty or quality specification. All materials may present unknown hazards, and should be used with caution. Although certain hazards are described, we cannot guarantee that these are the only hazards which exist. PerkinElmer shall not be held liable for any damage resulting from handling or from contact with the product.

· **Department issuing SDS:** Environmental, Health and Safety

· **Contact:**

Within the USA: 1-(800)-762-4000

Outside the USA: 1-(203)-712-8488

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 12)

acc. to OSHA HCS

Printing date 05/13/2021

Review date 05/13/2021

Trade name: WAV CALIBRATION P-2 TEST MIX

(Contd. of page 11)

IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
· *** Data compared to the previous version altered.**

USA