

acc. to OSHA HCS

Printing date 08/05/2019

Review date 04/18/2019

1 Identification

- **Product identifier**
- **Trade name:** WAVCALIBRATION P-40 TEST MIX
- **Article number** N0681470
- **Application of the substance / the mixture** Laboratory chemicals
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**

PerkinElmer, Inc.
710 Bridgeport Avenue
Shelton, Connecticut 06484 USA
CustomerCareUS@perkinelmer.com
203-925-4600

- **Emergency telephone number:**
CHEMTREC (within US) 800-424-9300
CHEMTREC (from outside US) +1 703-527-3887 (call collect)
CHEMTREC (within AU) +(61)-290372994

2 Hazard(s) identification

- **Classification of the substance or mixture**



Corrosion

Eye Dam. 1 H318 Causes serious eye damage.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms** GHS05
- **Signal word** Danger
- **Hazard-determining components of labeling:**
Hydrochloric Acid
- **Hazard statements**
H318 Causes serious eye damage.
- **Precautionary statements**
P280 Wear eye protection / face protection.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a poison center/doctor.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 3
Fire = 0
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = *3
Fire = 0
Reactivity = 0

(Contd. on page 2)

acc. to OSHA HCS

Printing date 08/05/2019

Review date 04/18/2019

Trade name: WAVCALIBRATION P-40 TEST MIX

(Contd. of page 1)

· **Other hazards**

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Substances**

· **CAS No. Description**

7732-18-5 Water

· **Identification number(s)**

· **EC number:** 231-791-2














· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Hazardous components:**

7647-01-0	Hydrochloric Acid	 Skin Corr. 1B, H314; Eye Dam. 1, H318  Acute Tox. 4, H302; STOT SE 3, H335	5.0%
-----------	-------------------	---	------

· **Additional Components**

7439-96-5	manganese		0.02%
7439-98-7	molybdenum		0.02%
7440-02-0	nickel	 Carc. 2, H351; STOT RE 1, H372  Skin Sens. 1, H317	0.02%
12060-08-1	scandium oxide		0.02%
7440-38-2	Arsenic	 Acute Tox. 3, H301; Acute Tox. 3, H331  Carc. 1A, H350  Aquatic Acute 1, H400; Aquatic Chronic 1, H410	0.02%
7439-91-0	lanthanum		0.02%
7440-23-5	sodium	 Water-react. 1, H260  Skin Corr. 1B, H314	0.02%
7439-93-2	lithium	 Water-react. 1, H260  Skin Corr. 1B, H314	0.02%
7440-09-7	potassium	 Water-react. 1, H260  Skin Corr. 1B, H314	0.01%
7723-14-0	red phosphorus	 Flam. Liq. 2, H225; Flam. Sol. 1, H228 Aquatic Chronic 3, H412	0.01%
7704-34-9	sulfur	 Skin Irrit. 2, H315	0.01%
7732-18-5	Water		94.81%

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

(Contd. on page 3)

acc. to OSHA HCS

Printing date 08/05/2019

Review date 04/18/2019

Trade name: WAVCALIBRATION P-40 TEST MIX

(Contd. of page 2)

- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

7647-01-0	Hydrochloric Acid	1.8 ppm
7439-96-5	manganese	3 mg/m ³
7439-98-7	molybdenum	30 mg/m ³
7440-02-0	nickel	4.5 mg/m ³
12060-08-1	scandium oxide	30 mg/m ³
7440-38-2	Arsenic	1.5 mg/m ³
7439-91-0	lanthanum	30 mg/m ³
7440-23-5	sodium	13 mg/m ³
7439-93-2	lithium	3.3 mg/m ³
7440-09-7	potassium	2.3 mg/m ³
7723-14-0	red phosphorus	0.27 mg/m ³

· PAC-2:

7647-01-0	Hydrochloric Acid	22 ppm
7439-96-5	manganese	5 mg/m ³

(Contd. on page 4)

acc. to OSHA HCS

Printing date 08/05/2019

Review date 04/18/2019

Trade name: WAVCALIBRATION P-40 TEST MIX

(Contd. of page 3)

7439-98-7	molybdenum	330 mg/m ³
7440-02-0	nickel	50 mg/m ³
12060-08-1	scandium oxide	330 mg/m ³
7440-38-2	Arsenic	17 mg/m ³
7439-91-0	lanthanum	330 mg/m ³
7440-23-5	sodium	140 mg/m ³
7439-93-2	lithium	36 mg/m ³
7440-09-7	potassium	25 mg/m ³
7723-14-0	red phosphorus	3 mg/m ³

· PAC-3:

7647-01-0	Hydrochloric Acid	100 ppm
7439-96-5	manganese	1,800 mg/m ³
7439-98-7	molybdenum	2,000 mg/m ³
7440-02-0	nickel	99 mg/m ³
12060-08-1	scandium oxide	2,000 mg/m ³
7440-38-2	Arsenic	100 mg/m ³
7439-91-0	lanthanum	2,000 mg/m ³
7440-23-5	sodium	870 mg/m ³
7439-93-2	lithium	220 mg/m ³
7440-09-7	potassium	150 mg/m ³
7723-14-0	red phosphorus	18 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

7647-01-0 Hydrochloric Acid	
PEL	Ceiling limit value: 7 mg/m ³ , 5 ppm

(Contd. on page 5)

acc. to OSHA HCS

Printing date 08/05/2019

Review date 04/18/2019

Trade name: WAVCALIBRATION P-40 TEST MIX

(Contd. of page 4)

REL	Ceiling limit value: 7 mg/m ³ , 5 ppm
TLV	Ceiling limit value: 2.98 mg/m ³ , 2 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:** Not required.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles or safety glasses

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: Transparent

· **Odor:** Odorless

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: 0 °C (32 °F)

(Contd. on page 6)

acc. to OSHA HCS

Printing date 08/05/2019

Review date 04/18/2019

Trade name: WAVCALIBRATION P-40 TEST MIX

(Contd. of page 5)

Boiling point/Boiling range:	100 °C (212 °F)
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard. Not determined.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
· Density at 20 °C (68 °F):	1 g/cm ³ (8.345 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Water:	94.8 %
VOC content:	0.00 %
Solids content:	3.1 %
· Other information	No further relevant information available.

*

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

USA

(Contd. on page 7)

acc. to OSHA HCS

Printing date 08/05/2019

Review date 04/18/2019

Trade name: WAVCALIBRATION P-40 TEST MIX

(Contd. of page 6)

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· Primary irritant effect:

· on the skin: No irritant effect.

· on the eye: Strong irritant with the danger of severe eye injury.

· Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

7647-01-0	Hydrochloric Acid	3
7440-02-0	nickel	2B
7440-38-2	Arsenic	1

· NTP (National Toxicology Program)

7440-02-0	nickel	R
7440-38-2	Arsenic	K

· OSHA-Ca (Occupational Safety & Health Administration)

7440-38-2	Arsenic
-----------	---------

12 Ecological information

· Toxicity

· Aquatic toxicity: No further relevant information available.

· Persistence and degradability No further relevant information available.

· Behavior in environmental systems:

· Bioaccumulative potential No further relevant information available.

· Mobility in soil No further relevant information available.

· Additional ecological information:

· General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Dispose of container and materials in accordance with local, regional and national regulations.

(Contd. on page 8)

acc. to OSHA HCS

Printing date 08/05/2019




Review date 04/18/2019

Trade name: WAVCALIBRATION P-40 TEST MIX

(Contd. of page 7)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	
· DOT, ADR, IMDG, IATA	UN1789
· UN proper shipping name	
· DOT	Hydrochloric acid
· ADR	1789 HYDROCHLORIC ACID HYDROCHLORIC ACID SOLUTION
· IMDG, IATA	HYDROCHLORIC ACID
· Transport hazard class(es)	
· DOT	
	
· Class	8 Corrosive substances
· Label	8
· ADR	
	
· Class	8 (C1) Corrosive substances
· Label	8
· IMDG, IATA	
	
· Class	8 Corrosive substances
· Label	8
· Packing group	
· DOT, ADR, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Corrosive substances
· Danger code (Kemler):	80
· EMS Number:	F-A,S-B
· Segregation groups	Strong acids

(Contd. on page 9)

acc. to OSHA HCS

Printing date 08/05/2019

Review date 04/18/2019



Trade name: WAVCALIBRATION P-40 TEST MIX

(Contd. of page 8)

· Stowage Category	C
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L
· ADR	
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1789 HYDROCHLORIC ACID, 8, II

*

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture			
7732-18-5	Water		94.81%
7647-01-0	Hydrochloric Acid	 Skin Corr. 1B, H314; Eye Dam. 1, H318  Acute Tox. 4, H302; STOT SE 3, H335	5.0%
7439-98-7	molybdenum		0.02%
· Sara			
· Section 355 (extremely hazardous substances):			
7647-01-0	Hydrochloric Acid		
7723-14-0	red phosphorus		
· Section 313 (Specific toxic chemical listings):			
7647-01-0	Hydrochloric Acid		
7439-96-5	manganese		
7440-02-0	nickel		
7440-38-2	Arsenic		
7723-14-0	red phosphorus		
· TSCA (Toxic Substances Control Act):			
All ingredients are listed.			
7647-01-0	Hydrochloric Acid		ACTIVE
7439-96-5	manganese		ACTIVE
7439-98-7	molybdenum		ACTIVE

(Contd. on page 10)

acc. to OSHA HCS

Printing date 08/05/2019

Review date 04/18/2019

Trade name: WAVCALIBRATION P-40 TEST MIX

(Contd. of page 9)

7440-02-0	nickel	ACTIVE
12060-08-1	scandium oxide	ACTIVE
7440-38-2	Arsenic	ACTIVE
7439-91-0	lanthanum	ACTIVE
7440-23-5	sodium	ACTIVE
7439-93-2	lithium	ACTIVE
7440-09-7	potassium	ACTIVE
7723-14-0	red phosphorus	ACTIVE
7704-34-9	sulfur	ACTIVE
7732-18-5	Water	ACTIVE

· **Hazardous Air Pollutants**

7647-01-0	Hydrochloric Acid
7439-96-5	manganese
7723-14-0	red phosphorus

· **Proposition 65**

· **Chemicals known to cause cancer:**

7440-02-0	nickel
7440-38-2	Arsenic

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

7439-96-5	manganese	D
7440-38-2	Arsenic	A
7723-14-0	red phosphorus	D

· **TLV (Threshold Limit Value established by ACGIH)**

7647-01-0	Hydrochloric Acid	A4
7439-98-7	molybdenum	A3
7440-02-0	nickel	A5
7440-38-2	Arsenic	A1

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

7440-02-0	nickel
7440-38-2	Arsenic

(Contd. on page 11)

acc. to OSHA HCS

Printing date 08/05/2019

Review date 04/18/2019

Trade name: WAVCALIBRATION P-40 TEST MIX

(Contd. of page 10)

- **National regulations:**
- **Information about limitation of use:**
Workers are not allowed to be exposed to this hazardous material. Exceptions can be made by the authorities in certain cases.
- **Water hazard class:** *Water hazard class 1 (Self-assessment): slightly hazardous for water.*
- **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

Disclaimer

The information provided in this Material Safety Data Sheet is based on our present knowledge, and believed to be correct at the date of publication. However, no representation is made concerning its accuracy and completeness. It is intended as guidance only, and is not to be considered a warranty or quality specification. All materials may present unknown hazards, and should be used with caution. Although certain hazards are described, we cannot guarantee that these are the only hazards which exist. PerkinElmer shall not be held liable for any damage resulting from handling or from contact with the product.

- **Department issuing SDS:** *Environmental, Health and Safety*

- **Contact:**

Within the USA: 1-(800)-762-4000

Outside the USA: 1-(203)-712-8488

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

- *** Data compared to the previous version altered.**