

09/19/2018

Kit Components

Product code	Description
N0690311	SOLUTION KIT-ZOD INSTALL
Components:	
N0582152	WAV CALIBRATION P-2 TEST MIX
N0773120	OPTIMA BLANK SOLUTION
N0691580	STD ZOD LOW UV
N0691581	STD ZOD-CA STRAY LIGHT
N9300221	FIVE ELEMENT A/S STD CAL 4
N9302946	WAVECALMIX VIS ZODIAC
N0691743	Optima family vis alignment solution
N0691745	MAGNESIUM STRAY LIGHT STANDARD
N0691579	STD ZOD MULTIELEMENT

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

1 Identification

- **Product identifier**
- **Trade name:** WAV CALIBRATION P-2 TEST MIX
- **Article number** N0582152
- **Application of the substance / the mixture** Laboratory chemicals
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**

PerkinElmer, Inc.
710 Bridgeport Avenue
Shelton, Connecticut 06484 USA
CustomerCareUS@perkinelmer.com
203-925-4600

- **Emergency telephone number:**
CHEMTREC (within US) 800-424-9300
CHEMTREC (from outside US) +1 703-527-3887 (call collect)
CHEMTREC (within AU) +(61)-290372994

2 Hazard(s) identification

- **Classification of the substance or mixture**
The product is not classified, according to the Globally Harmonized System (GHS).

- **Label elements**
- **GHS label elements** Void
- **Hazard pictograms** Void
- **Signal word** Void
- **Hazard statements** Void
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

HEALTH	0	Health = 0
FIRE	0	Fire = 0
REACTIVITY	0	Reactivity = 0

- **Other hazards**
The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: WAV CALIBRATION P-2 TEST MIX

(Contd. of page 1)













3 Composition/information on ingredients

- **Chemical characterization: Substances**
- **CAS No. Description**
7732-18-5 Water
- **Identification number(s)**
- **EC number: 231-791-2**
- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Hazardous components:

7647-01-0	Hydrochloric Acid	 Skin Corr. 1B, H314  STOT SE 3, H335	5.0%
-----------	-------------------	--	------

· Additional Components

7723-14-0	red phosphorus	0.01%
	 Flam. Liq. 2, H225; Flam. Sol. 1, H228	
7783-20-2	ammonium sulphate	0.01%
	 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	
7440-09-7	potassium	0.01%
	 Water-react. 1, H260	
	 Skin Corr. 1B, H314	
7439-93-2	lithium	0.002%
	 Water-react. 1, H260	
	 Skin Corr. 1B, H314	
7439-96-5	manganese	0.002%
7439-98-7	molybdenum	0.002%
7440-02-0	nickel	0.002%
	 Carc. 2, H351; STOT RE 1, H372	
	 Skin Sens. 1, H317	
7440-20-2	Scandium from Scandium Oxide	0.002%
7440-23-5	sodium	0.002%
	 Water-react. 1, H260	
	 Skin Corr. 1B, H314	
7440-38-2	Arsenic	0.002%
	 Acute Tox. 3, H301; Acute Tox. 3, H331	
	 Carc. 1A, H350	
7439-91-0	lanthanum	0.002%
7440-70-2	calcium	0.0001%
	 Water-react. 2, H261	
7732-18-5	Water	94.9539%

4 First-aid measures

- **Description of first aid measures**
- **General information:** No special measures required.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.

(Contd. on page 3)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: WAV CALIBRATION P-2 TEST MIX

(Contd. of page 2)

- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

7647-01-0	Hydrochloric Acid	1.8 ppm
7723-14-0	red phosphorus	0.27 mg/m ³
7783-20-2	ammonium sulphate	13 mg/m ³
7440-09-7	potassium	2.3 mg/m ³
7439-93-2	lithium	3.3 mg/m ³
7439-96-5	manganese	3 mg/m ³
7439-98-7	molybdenum	30 mg/m ³
7440-02-0	nickel	4.5 mg/m ³
7440-20-2	Scandium from Scandium Oxide	30 mg/m ³
7440-23-5	sodium	13 mg/m ³
7440-38-2	Arsenic	1.5 mg/m ³
7439-91-0	lanthanum	30 mg/m ³

· PAC-2:

7647-01-0	Hydrochloric Acid	22 ppm
7723-14-0	red phosphorus	3 mg/m ³
7783-20-2	ammonium sulphate	140 mg/m ³

(Contd. on page 4)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: WAV CALIBRATION P-2 TEST MIX

(Contd. of page 3)

7440-09-7	potassium	25 mg/m ³
7439-93-2	lithium	36 mg/m ³
7439-96-5	manganese	5 mg/m ³
7439-98-7	molybdenum	330 mg/m ³
7440-02-0	nickel	50 mg/m ³
7440-20-2	Scandium from Scandium Oxide	330 mg/m ³
7440-23-5	sodium	140 mg/m ³
7440-38-2	Arsenic	17 mg/m ³
7439-91-0	lanthanum	330 mg/m ³

PAC-3:

7647-01-0	Hydrochloric Acid	100 ppm
7723-14-0	red phosphorus	18 mg/m ³
7783-20-2	ammonium sulphate	840 mg/m ³
7440-09-7	potassium	150 mg/m ³
7439-93-2	lithium	220 mg/m ³
7439-96-5	manganese	1,800 mg/m ³
7439-98-7	molybdenum	2,000 mg/m ³
7440-02-0	nickel	99 mg/m ³
7440-20-2	Scandium from Scandium Oxide	2,000 mg/m ³
7440-23-5	sodium	870 mg/m ³
7440-38-2	Arsenic	100 mg/m ³
7439-91-0	lanthanum	2,000 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special measures required.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 5)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: WAV CALIBRATION P-2 TEST MIX

(Contd. of page 4)

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

7647-01-0 Hydrochloric Acid

PEL Ceiling limit value: 7 mg/m³, 5 ppm

REL Ceiling limit value: 7 mg/m³, 5 ppm

TLV Ceiling limit value: 2.98 mg/m³, 2 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

· **Breathing equipment:** Not required.

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Goggles recommended during refilling.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: Transparent

· **Odor:** Odorless

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: 0 °C (32 °F)

Boiling point/Boiling range: 100 °C (212 °F)

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not applicable.

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

(Contd. on page 6)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: WAV CALIBRATION P-2 TEST MIX

(Contd. of page 5)

· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
· Density at 20 °C (68 °F):	1 g/cm ³ (8.345 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Water:	95.0 %
VOC content:	0.00 %
Solids content:	3.1 %
· Other information	No further relevant information available.

*

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

*

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**
 - **Primary irritant effect:**
 - on the skin:** No irritant effect.
 - on the eye:** No irritating effect.
 - **Sensitization:** No sensitizing effects known.
 - **Additional toxicological information:**
- The product is not subject to classification according to internally approved calculation methods for preparations:
- When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

(Contd. on page 7)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: WAV CALIBRATION P-2 TEST MIX

(Contd. of page 6)

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

7647-01-0	Hydrochloric Acid	3
7440-02-0	nickel	2B
7440-38-2	Arsenic	I

· **NTP (National Toxicology Program)**

7440-02-0	nickel	R
7440-38-2	Arsenic	K

· **OSHA-Ca (Occupational Safety & Health Administration)**

7440-38-2	Arsenic	
-----------	---------	--

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:** Smaller quantities can be disposed of with household waste.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· **DOT, ADR, IMDG, IATA** UN1789

· **UN proper shipping name**

· **DOT** Hydrochloric acid
· **ADR** 1789 Hydrochloric acid
HYDROCHLORIC ACID, solution

(Contd. on page 8)




acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: WAV CALIBRATION P-2 TEST MIX

(Contd. of page 7)

· IMDG, IATA	HYDROCHLORIC ACID
· Transport hazard class(es)	
· DOT	
	
· Class	8 Corrosive substances
· Label	8
· ADR	
	
· Class	8 (C1) Corrosive substances
· Label	8
· IMDG, IATA	
	
· Class	8 Corrosive substances
· Label	8
· Packing group	
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Corrosive substances
· Danger code (Kemler):	80
· EMS Number:	F-A,S-B
· Segregation groups	Acids
· Stowage Category	E
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· ADR	
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 9)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: WAV CALIBRATION P-2 TEST MIX

(Contd. of page 8)

- **IMDG**
- **Limited quantities (LQ)** 5L
- **Excepted quantities (EQ)** Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
- **UN "Model Regulation":** UN 1789 HYDROCHLORIC ACID, 8, III

*

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

7732-18-5	Water	94.9539%
7647-01-0	Hydrochloric Acid ⚠ Skin Corr. 1B, H314 ⚠ STOT SE 3, H335	5.0%
7783-20-2	ammonium sulphate ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	0.01%

· Sara

· Section 355 (extremely hazardous substances):

7647-01-0	Hydrochloric Acid
7723-14-0	red phosphorus

· Section 313 (Specific toxic chemical listings):

7647-01-0	Hydrochloric Acid
7723-14-0	red phosphorus
7783-20-2	ammonium sulphate
7439-96-5	manganese
7440-02-0	nickel
7440-38-2	Arsenic

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

7647-01-0	Hydrochloric Acid
7723-14-0	red phosphorus
7783-20-2	ammonium sulphate
7440-09-7	potassium
7439-93-2	lithium
7439-96-5	manganese
7439-98-7	molybdenum
7440-02-0	nickel
7440-20-2	Scandium from Scandium Oxide
7440-23-5	sodium
7440-38-2	Arsenic

(Contd. on page 10)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: WAV CALIBRATION P-2 TEST MIX

(Contd. of page 9)

7439-91-0	lanthanum
7440-70-2	calcium
7732-18-5	Water

· **Proposition 65**

· **Chemicals known to cause cancer:**

7440-02-0	nickel
7440-38-2	Arsenic

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogen categories**

· **EPA (Environmental Protection Agency)**

7723-14-0	red phosphorus	D
7439-96-5	manganese	D
7440-38-2	Arsenic	A

· **TLV (Threshold Limit Value established by ACGIH)**

7647-01-0	Hydrochloric Acid	A4
7439-98-7	molybdenum	A3
7440-02-0	nickel	A5
7440-38-2	Arsenic	A1

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

7440-02-0	nickel
7440-38-2	Arsenic

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to this hazardous material. Exceptions can be made by the authorities in certain cases.

· **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

Disclaimer

The information provided in this Material Safety Data Sheet is based on our present knowledge, and believed to be correct at the date of publication. However, no representation is made concerning its accuracy and completeness. It is intended as guidance only, and is not to be considered a warranty or quality specification. All materials may present unknown hazards, and should be used with caution. Although certain hazards are described, we cannot guarantee that these are the only hazards which exist. PerkinElmer shall not be held

(Contd. on page 11)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: WAV CALIBRATION P-2 TEST MIX

(Contd. of page 10)

liable for any damage resulting from handling or from contact with the product.

· **Department issuing SDS:** Environmental, Health and Safety

· **Contact:**

Within the USA: 1-(800)-762-4000

Outside the USA: 1-(203)-712-8488

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· *** Data compared to the previous version altered.**

USA

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

1 Identification

- **Product identifier**
- **Trade name:** **OPTIMA BLANK SOLUTION**
- **Article number** N0773120
- **Application of the substance / the mixture** Laboratory chemicals
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**

PerkinElmer, Inc.
710 Bridgeport Avenue
Shelton, Connecticut 06484 USA
CustomerCareUS@perkinelmer.com
203-925-4600

- **Emergency telephone number:**
CHEMTREC (within US) 800-424-9300
CHEMTREC (from outside US) +1 703-527-3887 (call collect)
CHEMTREC (within AU) +(61)-290372994

2 Hazard(s) identification

- **Classification of the substance or mixture**



Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms** GHS07
- **Signal word** Warning
- **Hazard statements**
H315 Causes skin irritation.
H319 Causes serious eye irritation.
- **Precautionary statements**
P264 Wash thoroughly after handling.
P280 Wear protective gloves / eye protection / face protection.
P302+P352 If on skin: Wash with plenty of water.
P321 Specific treatment (see on this label).
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P337+P313 If eye irritation persists: Get medical advice/attention.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 0
Reactivity = 0

(Contd. on page 2)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: OPTIMA BLANK SOLUTION

(Contd. of page 1)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	0	Fire = 0
REACTIVITY	0	Reactivity = 0

· **Other hazards**

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Substances**

· **CAS No. Description**

7732-18-5 Water

· **Identification number(s)**

· **EC number:** 231-791-2

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Hazardous components:**

7697-37-2	Nitric Acid	 Ox. Liq. 2, H272	2.0%
		 Skin Corr. 1A, H314	

· **Additional Components**

7732-18-5	Water	98.0%
-----------	-------	-------

4 First-aid measures

· **Description of first aid measures**

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.

· **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 3)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: **OPTIMA BLANK SOLUTION**

(Contd. of page 2)

- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

7697-37-2	Nitric Acid	0.16 ppm
-----------	-------------	----------

· PAC-2:

7697-37-2	Nitric Acid	24 ppm
-----------	-------------	--------

· PAC-3:

7697-37-2	Nitric Acid	92 ppm
-----------	-------------	--------

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 4)

USA

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: OPTIMA BLANK SOLUTION

(Contd. of page 3)

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

7697-37-2 Nitric Acid

PEL	Long-term value: 5 mg/m ³ , 2 ppm
REL	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5 mg/m ³ , 2 ppm
TLV	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5.2 mg/m ³ , 2 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

· **Breathing equipment:** Not required.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles or safety glasses

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Liquid
Color:	Transparent
Odor:	Odorless

(Contd. on page 5)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: OPTIMA BLANK SOLUTION

(Contd. of page 4)

· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	0 °C (32 °F)
Boiling point/Boiling range:	100 °C (212 °F)
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
· Density at 20 °C (68 °F):	1 g/cm ³ (8.345 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Water:	98.0 %
VOC content:	0.00 %
· Other information	No further relevant information available.

*

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

USA

(Contd. on page 6)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: OPTIMA BLANK SOLUTION

(Contd. of page 5)

*

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**
 - **Primary irritant effect:**
 - **on the skin:** Irritant to skin and mucous membranes.
 - **on the eye:** Irritating effect.
 - **Sensitization:** No sensitizing effects known.
 - **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
 - **Carcinogenic categories**
- | |
|--|
| · IARC (International Agency for Research on Cancer) |
| None of the ingredients is listed. |
| · NTP (National Toxicology Program) |
| None of the ingredients is listed. |
| · OSHA-Ca (Occupational Safety & Health Administration) |
| None of the ingredients is listed. |

*

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Not hazardous for water.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

*

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**

Dispose of container and materials in accordance with local, regional and national regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

USA

(Contd. on page 7)

acc. to OSHA HCS







Printing date 09/19/2018

Review date 09/19/2018

Trade name: OPTIMA BLANK SOLUTION

(Contd. of page 6)

14 Transport information

· UN-Number	UN3264
· DOT, ADR, IMDG, IATA	
· UN proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s.
· DOT	3264 Corrosive liquid, acidic, inorganic, n.o.s. (nitric acid)
· ADR	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric Acid solution)
· IMDG	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid), MARINE POLLUTANT
· IATA	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid)
· Transport hazard class(es)	
· DOT	
	 
· Class	8 Corrosive substances
· Label	8
· ADR	
	
· Class	8 (C1) Corrosive substances
· Label	8
· IMDG	
	 
· Class	8 Corrosive substances
· Label	8
· IATA	
	
· Class	8 Corrosive substances
· Label	8
· Packing group	
· DOT, ADR, IMDG, IATA	III

(Contd. on page 8)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018



Trade name: OPTIMA BLANK SOLUTION

(Contd. of page 7)

· Environmental hazards:	
· Marine pollutant:	No Symbol (fish and tree)
· Special precautions for user	Warning: Corrosive substances
· Danger code (Kemler):	80
· EMS Number:	F-A,S-B
· Segregation groups	Acids
· Stowage Category	A
· Stowage Code	SW2 Clear of living quarters.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· Remarks:	Special marking with the symbol (fish and tree).
· ADR	
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID), 8, III

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

7732-18-5	Water		98.0%
7697-37-2	Nitric Acid	 Ox. Liq. 2, H272  Skin Corr. 1A, H314	2.0%

· **Sara**

· **Section 355 (extremely hazardous substances):**

7697-37-2	Nitric Acid
-----------	-------------

· **Section 313 (Specific toxic chemical listings):**

7697-37-2	Nitric Acid
-----------	-------------

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

7697-37-2	Nitric Acid
-----------	-------------

(Contd. on page 9)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: OPTIMA BLANK SOLUTION

(Contd. of page 8)

7732-18-5 | Water

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to this hazardous material. Exceptions can be made by the authorities in certain cases.

· **Water hazard class:** Generally not hazardous for water.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

*

16 Other information

Disclaimer

The information provided in this Material Safety Data Sheet is based on our present knowledge, and believed to be correct at the date of publication. However, no representation is made concerning its accuracy and completeness. It is intended as guidance only, and is not to be considered a warranty or quality specification. All materials may present unknown hazards, and should be used with caution. Although certain hazards are described, we cannot guarantee that these are the only hazards which exist. PerkinElmer shall not be held liable for any damage resulting from handling or from contact with the product.

· **Department issuing SDS:** Environmental, Health and Safety

· **Contact:**

Within the USA: 1-(800)-762-4000

Outside the USA: 1-(203)-712-8488

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 10)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: OPTIMA BLANK SOLUTION

(Contd. of page 9)

IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Ox. Liq. 2: Oxidizing liquids – Category 2
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
· *** Data compared to the previous version altered.**

USA

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

1 Identification

- **Product identifier**
- **Trade name:** STD ZOD LOW UV
- **Article number** N0691580
- **Application of the substance / the mixture** Laboratory chemicals
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**

PerkinElmer, Inc.
710 Bridgeport Avenue
Shelton, Connecticut 06484 USA
CustomerCareUS@perkinelmer.com
203-925-4600

- **Emergency telephone number:**
CHEMTREC (within US) 800-424-9300
CHEMTREC (from outside US) +1 703-527-3887 (call collect)
CHEMTREC (within AU) +(61)-290372994

2 Hazard(s) identification

- **Classification of the substance or mixture**



Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms** GHS07
- **Signal word** Warning
- **Hazard statements**
H315 Causes skin irritation.
H319 Causes serious eye irritation.
- **Precautionary statements**
P264 Wash thoroughly after handling.
P280 Wear protective gloves / eye protection / face protection.
P302+P352 If on skin: Wash with plenty of water.
P321 Specific treatment (see on this label).
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P337+P313 If eye irritation persists: Get medical advice/attention.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 0
Reactivity = 0

(Contd. on page 2)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: STD ZOD LOW UV

(Contd. of page 1)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	0	Fire = 0
REACTIVITY	0	Reactivity = 0

· **Other hazards**

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.



3 Composition/information on ingredients

- **Chemical characterization: Substances**
- **CAS No. Description**
7732-18-5 Water
- **Identification number(s)**
- **EC number:** 231-791-2
- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Hazardous components:**

7697-37-2	Nitric Acid	 Ox. Liq. 2, H272  Skin Corr. 1A, H314	2.0%
-----------	-------------	---	------

· **Additional Components**

7723-14-0	red phosphorus	 Flam. Liq. 2, H225; Flam. Sol. 1, H228	0.001%
7704-34-9	sulfur	 Skin Irrit. 2, H315	0.001%
7429-90-5	aluminium		0.001%
7732-18-5	Water		97.997%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

USA

(Contd. on page 3)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: STD ZOD LOW UV

(Contd. of page 2)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

7697-37-2	Nitric Acid	0.16 ppm
7723-14-0	red phosphorus	0.27 mg/m ³

· PAC-2:

7697-37-2	Nitric Acid	24 ppm
7723-14-0	red phosphorus	3 mg/m ³

· PAC-3:

7697-37-2	Nitric Acid	92 ppm
7723-14-0	red phosphorus	18 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

USA

(Contd. on page 4)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: STD ZOD LOW UV

(Contd. of page 3)

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

7697-37-2 Nitric Acid

PEL	Long-term value: 5 mg/m ³ , 2 ppm
REL	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5 mg/m ³ , 2 ppm
TLV	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5.2 mg/m ³ , 2 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:** Not required.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles or safety glasses

USA

(Contd. on page 5)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: STD ZOD LOW UV

(Contd. of page 4)

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Color:	Transparent
Odor:	Odorless
Odor threshold:	Not determined.

· pH-value at 20 °C (68 °F): >2

· Change in condition

Melting point/Melting range:	0 °C (32 °F)
Boiling point/Boiling range:	100 °C (212 °F)

· Flash point: Not applicable.

· Flammability (solid, gaseous): Not applicable.

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower:	Not determined.
Upper:	Not determined.

· Vapor pressure at 20 °C (68 °F): 23 hPa (17.3 mm Hg)

· Density at 20 °C (68 °F): 1 g/cm³ (8.345 lbs/gal)

· Relative density: Not determined.

· Vapor density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

· Solvent content:

Water: 98.0 %

VOC content: 0.00 %

· Other information: No further relevant information available.

10 Stability and reactivity

· Reactivity: No further relevant information available.

· Chemical stability

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 6)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: STD ZOD LOW UV

(Contd. of page 5)

- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Not hazardous for water.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Dispose of container and materials in accordance with local, regional and national regulations.

(Contd. on page 7)

acc. to OSHA HCS

Printing date 09/19/2018




Review date 09/19/2018

Trade name: STD ZOD LOW UV

(Contd. of page 6)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	UN3264
· DOT, ADR, IMDG, IATA	
· UN proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric Acid)
· DOT	3264 Corrosive liquid, acidic, inorganic, n.o.s. (Nitric Acid)
· ADR	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric Acid)
· IMDG, IATA	
· Transport hazard class(es)	
· DOT	
	
· Class	8 Corrosive substances
· Label	8
· ADR	
	
· Class	8 (C1) Corrosive substances
· Label	8
· IMDG, IATA	
	
· Class	8 Corrosive substances
· Label	8
· Packing group	III
· DOT, ADR, IMDG, IATA	
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Corrosive substances
· Danger code (Kemler):	80
· EMS Number:	F-A,S-B
· Segregation groups	Acids
· Stowage Category	A

(Contd. on page 8)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018




Trade name: STD ZOD LOW UV

(Contd. of page 7)

· Stowage Code	SW2 Clear of living quarters.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· ADR	
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID), 8, III

*

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture			
7732-18-5	Water		97.997%
7697-37-2	Nitric Acid	 Ox. Liq. 2, H272  Skin Corr. 1A, H314	2.0%
7704-34-9	sulfur	 Skin Irrit. 2, H315	0.001%
· Sara			
· Section 355 (extremely hazardous substances):			
7697-37-2	Nitric Acid		
7723-14-0	red phosphorus		
· Section 313 (Specific toxic chemical listings):			
7697-37-2	Nitric Acid		
7723-14-0	red phosphorus		
7429-90-5	aluminium		
· TSCA (Toxic Substances Control Act):			
All ingredients are listed.			
7697-37-2	Nitric Acid		
7723-14-0	red phosphorus		
7704-34-9	sulfur		
7429-90-5	aluminium		
7732-18-5	Water		

(Contd. on page 9)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: STD ZOD LOW UV

(Contd. of page 8)

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

7723-14-0 red phosphorus

D

· **TLV (Threshold Limit Value established by ACGIH)**

7429-90-5 aluminium

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to this hazardous material. Exceptions can be made by the authorities in certain cases.

· **Water hazard class:** Generally not hazardous for water.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

Disclaimer

The information provided in this Material Safety Data Sheet is based on our present knowledge, and believed to be correct at the date of publication. However, no representation is made concerning its accuracy and completeness. It is intended as guidance only, and is not to be considered a warranty or quality specification. All materials may present unknown hazards, and should be used with caution. Although certain hazards are described, we cannot guarantee that these are the only hazards which exist. PerkinElmer shall not be held liable for any damage resulting from handling or from contact with the product.

· **Department issuing SDS:** Environmental, Health and Safety

· **Contact:**

Within the USA: 1-(800)-762-4000

Outside the USA: 1-(203)-712-8488

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

(Contd. on page 10)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: STD ZOD LOW UV

(Contd. of page 9)

IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Ox. Liq. 2: Oxidizing liquids – Category 2
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

*** Data compared to the previous version altered.**

USA

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

1 Identification

- **Product identifier**
- **Trade name:** STD ZOD-CA STRAY LIGHT
- **Article number** N0691581
- **Application of the substance / the mixture** Laboratory chemicals
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**

PerkinElmer, Inc.
710 Bridgeport Avenue
Shelton, Connecticut 06484 USA
CustomerCareUS@perkinelmer.com
203-925-4600

- **Emergency telephone number:**
CHEMTREC (within US) 800-424-9300
CHEMTREC (from outside US) +1 703-527-3887 (call collect)
CHEMTREC (within AU) +(61)-290372994

2 Hazard(s) identification

- **Classification of the substance or mixture**



Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms** GHS05
- **Signal word** Danger

- **Hazard-determining components of labeling:**

Nitric Acid

- **Hazard statements**

H314 Causes severe skin burns and eye damage.

- **Precautionary statements**

P260 Do not breathe dusts or mists.
P264 Wash thoroughly after handling.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a poison center/doctor.
P321 Specific treatment (see on this label).
P363 Wash contaminated clothing before reuse.
P405 Store locked up.

(Contd. on page 2)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: STD ZOD-CA STRAY LIGHT

(Contd. of page 1)

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**

HEALTH	3	Health = 3
FIRE	0	Fire = 0
REACTIVITY	0	Reactivity = 0

· **Other hazards**

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Substances**

· **CAS No. Description**

7732-18-5 Water

· **Identification number(s)**

· **EC number:** 231-791-2

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Hazardous components:**

7697-37-2	Nitric Acid	Ox. Liq. 2, H272	5.0%
		Skin Corr. 1A, H314	
7440-70-2	calcium	Water-react. 2, H261	1.0%

· **Additional Components**

7732-18-5	Water	94.0%
-----------	-------	-------

4 First-aid measures

· **Description of first aid measures**

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: STD ZOD-CA STRAY LIGHT

(Contd. of page 2)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

7697-37-2	Nitric Acid	0.16 ppm
-----------	-------------	----------

· PAC-2:

7697-37-2	Nitric Acid	24 ppm
-----------	-------------	--------

· PAC-3:

7697-37-2	Nitric Acid	92 ppm
-----------	-------------	--------

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
The product is not flammable.

(Contd. on page 4)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: STD ZOD-CA STRAY LIGHT

(Contd. of page 3)

Keep respiratory protective device available.

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

7697-37-2 Nitric Acid

PEL	Long-term value: 5 mg/m ³ , 2 ppm
REL	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5 mg/m ³ , 2 ppm
TLV	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5.2 mg/m ³ , 2 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: STD ZOD-CA STRAY LIGHT

(Contd. of page 4)

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles or safety glasses

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: Transparent

· **Odor:** Odorless

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: 0 °C (32 °F)

Boiling point/Boiling range: 100 °C (212 °F)

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not applicable.

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

Lower: Not determined.

Upper: Not determined.

· **Vapor pressure at 20 °C (68 °F):** 23 hPa (17.3 mm Hg)

· **Density at 20 °C (68 °F):** 1 g/cm³ (8.345 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

Water: Fully miscible.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic: Not determined.

Kinematic: Not determined.

(Contd. on page 6)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: STD ZOD-CA STRAY LIGHT

(Contd. of page 5)

· Solvent content:	
Water:	94.0 %
VOC content:	0.00 %
· Solids content:	
Other information	1.0 %
No further relevant information available.	

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Caustic effect on skin and mucous membranes.
- **on the eye:**
Strong caustic effect.
Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Corrosive
Irritant
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.
- **Carcinogenic categories**
- **IARC (International Agency for Research on Cancer)**
None of the ingredients is listed.
- **NTP (National Toxicology Program)**
None of the ingredients is listed.
- **OSHA-Ca (Occupational Safety & Health Administration)**
None of the ingredients is listed.

USA

(Contd. on page 7)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: STD ZOD-CA STRAY LIGHT

(Contd. of page 6)

*

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.


*

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Dispose of container and materials in accordance with local, regional and national regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

*

14 Transport information

- | | |
|---|--|
| · UN-Number | |
| · DOT, ADR, IMDG, IATA | UN3264 |
| · UN proper shipping name | |
| · DOT | Corrosive liquid, acidic, inorganic, n.o.s. (nitric acid) |
| · ADR | 3264 Corrosive liquid, acidic, inorganic, n.o.s. (nitric acid) |
| · IMDG, IATA | CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid) |
| · Transport hazard class(es) | |
| · DOT | |
|  | |
| · Class | 8 Corrosive substances |

(Contd. on page 8)

USA



acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: STD ZOD-CA STRAY LIGHT

(Contd. of page 7)

· Label	8
· ADR	
	
· Class	8 (C1) Corrosive substances
· Label	8
· IMDG, IATA	
	
· Class	8 Corrosive substances
· Label	8
· Packing group	
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Corrosive substances
· Danger code (Kemler):	80
· EMS Number:	F-A,S-B
· Segregation groups	Acids
· Stowage Category	A
· Stowage Code	SW2 Clear of living quarters.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· ADR	
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 9)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018




Trade name: STD ZOD-CA STRAY LIGHT

(Contd. of page 8)

· **UN "Model Regulation":** UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID), 8, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

7732-18-5	Water		94.0%
7697-37-2	Nitric Acid	 Ox. Liq. 2, H272  Skin Corr. 1A, H314	5.0%
7440-70-2	calcium	 Water-react. 2, H261	1.0%

· Sara

· Section 355 (extremely hazardous substances):

7697-37-2	Nitric Acid
-----------	-------------

· Section 313 (Specific toxic chemical listings):

7697-37-2	Nitric Acid
-----------	-------------

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

7697-37-2	Nitric Acid
7440-70-2	calcium
7732-18-5	Water

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

(Contd. on page 10)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: STD ZOD-CA STRAY LIGHT

(Contd. of page 9)

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to this hazardous material. Exceptions can be made by the authorities in certain cases.

· **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

Disclaimer

The information provided in this Material Safety Data Sheet is based on our present knowledge, and believed to be correct at the date of publication. However, no representation is made concerning its accuracy and completeness. It is intended as guidance only, and is not to be considered a warranty or quality specification. All materials may present unknown hazards, and should be used with caution. Although certain hazards are described, we cannot guarantee that these are the only hazards which exist. PerkinElmer shall not be held liable for any damage resulting from handling or from contact with the product.

· **Department issuing SDS:** Environmental, Health and Safety

· **Contact:**

Within the USA: 1-(800)-762-4000

Outside the USA: 1-(203)-712-8488

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Water-react. 2: Substances and mixtures which in contact with water emit flammable gases – Category 2

Ox. Liq. 2: Oxidizing liquids – Category 2

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

· *** Data compared to the previous version altered.**

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

1 Identification

- **Product identifier**
- **Trade name:** FIVE ELEMENT A/S STD CAL 4
- **Article number** N9300221
- **Application of the substance / the mixture** Laboratory chemicals
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**

PerkinElmer, Inc.
710 Bridgeport Avenue
Shelton, Connecticut 06484 USA
CustomerCareUS@perkinelmer.com
203-925-4600

- **Emergency telephone number:**
CHEMTREC (within US) 800-424-9300
CHEMTREC (from outside US) +1 703-527-3887 (call collect)
CHEMTREC (within AU) +(61)-290372994

2 Hazard(s) identification

- **Classification of the substance or mixture**



Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms** GHS05
- **Signal word** Danger

- **Hazard-determining components of labeling:**

Nitric Acid

- **Hazard statements**

H314 Causes severe skin burns and eye damage.

- **Precautionary statements**

P260 Do not breathe dusts or mists.

P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

P321 Specific treatment (see on this label).

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

(Contd. on page 2)

USA

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: FIVE ELEMENT A/S STD CAL 4

(Contd. of page 1)

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Substances**

· **CAS No. Description**

7732-18-5 Water

· **Identification number(s)**

· **EC number:** 231-791-2

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Hazardous components:**

7697-37-2	Nitric Acid	Ox. Liq. 2, H272 Skin Corr. 1A, H314	5.0%
-----------	-------------	---	------

· **Additional Components**

7440-28-0	thallium Acute Tox. 2, H300; Acute Tox. 2, H330 STOT RE 2, H373	0.01%
7440-38-2	Arsenic Acute Tox. 3, H301; Acute Tox. 3, H331 Carc. 1A, H350	0.01%
7782-49-2	selenium Acute Tox. 3, H301; Acute Tox. 3, H331 STOT RE 2, H373	0.005%
7439-92-1	lead Acute Tox. 3, H301 Carc. 2, H351; Repr. 1A, H360-H362 Acute Tox. 4, H332	0.005%



(Contd. on page 3)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: FIVE ELEMENT A/S STD CAL 4

		(Contd. of page 2)
7440-43-9	cadmium (non-pyrophoric)	0.005%
	 Acute Tox. 2, H330  Muta. 2, H341; Carc. 1B, H350; Repr. 2, H361; STOT RE 1, H372	
7732-18-5	Water	94.965%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-I:**

7697-37-2	Nitric Acid	0.16 ppm
-----------	-------------	----------

(Contd. on page 4)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: FIVE ELEMENT A/S STD CAL 4

(Contd. of page 3)

7440-28-0	thallium	0.06 mg/m ³
7440-38-2	Arsenic	1.5 mg/m ³
7782-49-2	selenium	0.6 mg/m ³
7439-92-1	lead	0.15 mg/m ³
7440-43-9	cadmium (non-pyrophoric)	0.10 mg/m ³

· **PAC-2:**

7697-37-2	Nitric Acid	24 ppm
7440-28-0	thallium	3.3 mg/m ³
7440-38-2	Arsenic	17 mg/m ³
7782-49-2	selenium	6.6 mg/m ³
7439-92-1	lead	120 mg/m ³
7440-43-9	cadmium (non-pyrophoric)	0.76 mg/m ³

· **PAC-3:**

7697-37-2	Nitric Acid	92 ppm
7440-28-0	thallium	20 mg/m ³
7440-38-2	Arsenic	100 mg/m ³
7782-49-2	selenium	40 mg/m ³
7439-92-1	lead	700 mg/m ³
7440-43-9	cadmium (non-pyrophoric)	4.7 mg/m ³

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:** Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** No special requirements.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Keep receptacle tightly sealed.

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 5)

USA

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: FIVE ELEMENT A/S STD CAL 4

(Contd. of page 4)

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

7697-37-2 Nitric Acid

PEL	Long-term value: 5 mg/m ³ , 2 ppm
REL	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5 mg/m ³ , 2 ppm
TLV	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5.2 mg/m ³ , 2 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles or safety glasses

· **Body protection:** Apron

USA

(Contd. on page 6)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: FIVE ELEMENT A/S STD CAL 4

(Contd. of page 5)

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Color:	Transparent
Odor:	Characteristic
Odor threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:	0 °C (32 °F)
Boiling point/Boiling range:	100 °C (212 °F)

· Flash point: Not applicable.

· Flammability (solid, gaseous): Not applicable.

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower:	Not determined.
Upper:	Not determined.

· Vapor pressure at 20 °C (68 °F): 23 hPa (17.3 mm Hg)

· Density at 20 °C (68 °F): 1 g/cm³ (8.345 lbs/gal)

· Relative density: Not determined.

· Vapor density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with

Water: Fully miscible.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

· Solvent content:

Water: 95.0 %

VOC content: 0.00 %

· Other information: No further relevant information available.

10 Stability and reactivity

· Reactivity: No further relevant information available.

· Chemical stability

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 7)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: FIVE ELEMENT A/S STD CAL 4

(Contd. of page 6)

- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Caustic effect on skin and mucous membranes.
- **on the eye:**
Strong caustic effect.
Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Corrosive
Irritant
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.
- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)

7440-38-2	Arsenic	1
7782-49-2	selenium	3
7439-92-1	lead	2B
7440-43-9	cadmium (non-pyrophoric)	1

· NTP (National Toxicology Program)

7440-38-2	Arsenic	K
7439-92-1	lead	R
7440-43-9	cadmium (non-pyrophoric)	K

· OSHA-Ca (Occupational Safety & Health Administration)

7440-38-2	Arsenic
7440-43-9	cadmium (non-pyrophoric)

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 8)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: FIVE ELEMENT A/S STD CAL 4

(Contd. of page 7)

· **Additional ecological information:**

· **General notes:**

*Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.*

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Dispose of container and materials in accordance with local, regional and national regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

· **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· **UN-Number**

· **DOT, ADR, IMDG, IATA**

UN3264

· **UN proper shipping name**

· **DOT**

· **ADR**

Corrosive liquid, acidic, inorganic, n.o.s.

3264 Corrosive liquid, acidic, inorganic, n.o.s. (Nitric Acid)

CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric Acid solution)

· **IMDG**

CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric Acid), MARINE POLLUTANT

· **IATA**

CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric Acid)

· **Transport hazard class(es)**

· **DOT**



· **Class**

8 Corrosive substances

· **Label**

8

· **ADR**



· **Class**

8 (C1) Corrosive substances

(Contd. on page 9)



acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: FIVE ELEMENT A/S STD CAL 4

(Contd. of page 8)

· Label	8
· IMDG	
	
· Class	8 Corrosive substances
· Label	8
· IATA	
	
· Class	8 Corrosive substances
· Label	8
· Packing group	
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	No Symbol (fish and tree)
· Special precautions for user	Warning: Corrosive substances
· Danger code (Kemler):	80
· EMS Number:	F-A,S-B
· Segregation groups	Acids
· Stowage Category	A
· Stowage Code	SW2 Clear of living quarters.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· Remarks:	Special marking with the symbol (fish and tree).
· ADR	
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 10)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018





Trade name: FIVE ELEMENT A/S STD CAL 4

(Contd. of page 9)

· UN "Model Regulation": UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID), 8, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

7732-18-5	Water		94.965%
7697-37-2	Nitric Acid	 Ox. Liq. 2, H272  Skin Corr. 1A, H314	5.0%
7440-38-2	Arsenic	 Acute Tox. 3, H301; Acute Tox. 3, H331  Carc. 1A, H350	0.01%

· Sara

· Section 355 (extremely hazardous substances):

7697-37-2	Nitric Acid
-----------	-------------

· Section 313 (Specific toxic chemical listings):

7697-37-2	Nitric Acid
7440-28-0	thallium
7440-38-2	Arsenic
7782-49-2	selenium
7439-92-1	lead
7440-43-9	cadmium (non-pyrophoric)

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

7697-37-2	Nitric Acid
7440-28-0	thallium
7440-38-2	Arsenic
7782-49-2	selenium
7439-92-1	lead
7440-43-9	cadmium (non-pyrophoric)
7732-18-5	Water

· Proposition 65

· Chemicals known to cause cancer:

7440-38-2	Arsenic
7439-92-1	lead
7440-43-9	cadmium (non-pyrophoric)

· Chemicals known to cause reproductive toxicity for females:

7439-92-1	lead
-----------	------

· Chemicals known to cause reproductive toxicity for males:

7439-92-1	lead
7440-43-9	cadmium (non-pyrophoric)

(Contd. on page 11)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: FIVE ELEMENT A/S STD CAL 4

(Contd. of page 10)

· **Chemicals known to cause developmental toxicity:**

7439-92-1	lead
7440-43-9	cadmium (non-pyrophoric)

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

7440-38-2	Arsenic	A
7782-49-2	selenium	D
7439-92-1	lead	B2
7440-43-9	cadmium (non-pyrophoric)	B1

· **TLV (Threshold Limit Value established by ACGIH)**

7440-38-2	Arsenic	A1
7439-92-1	lead	A3
7440-43-9	cadmium (non-pyrophoric)	A2

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

7440-38-2	Arsenic
7440-43-9	cadmium (non-pyrophoric)

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to this hazardous material. Exceptions can be made by the authorities in certain cases.

· **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

Disclaimer

The information provided in this Material Safety Data Sheet is based on our present knowledge, and believed to be correct at the date of publication. However, no representation is made concerning its accuracy and completeness. It is intended as guidance only, and is not to be considered a warranty or quality specification. All materials may present unknown hazards, and should be used with caution. Although certain hazards are described, we cannot guarantee that these are the only hazards which exist. PerkinElmer shall not be held liable for any damage resulting from handling or from contact with the product.

· **Department issuing SDS:** Environmental, Health and Safety

· **Contact:**

Within the USA: 1-(800)-762-4000

Outside the USA: 1-(203)-712-8488

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

(Contd. on page 12)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: FIVE ELEMENT A/S STD CAL 4

(Contd. of page 11)

IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Ox. Liq. 2: Oxidizing liquids – Category 2
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Dam. 1: Serious eye damage/eye irritation – Category 1

*** Data compared to the previous version altered.**

USA

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

1 Identification

- **Product identifier**
- **Trade name:** WAVECALMIX VIS ZODIAC
- **Article number** N9302946
- **Application of the substance / the mixture** Laboratory chemicals
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**

PerkinElmer, Inc.
710 Bridgeport Avenue
Shelton, Connecticut 06484 USA
CustomerCareUS@perkinelmer.com
203-925-4600

- **Emergency telephone number:**
CHEMTREC (within US) 800-424-9300
CHEMTREC (from outside US) +1 703-527-3887 (call collect)
CHEMTREC (within AU) +(61)-290372994

2 Hazard(s) identification

- **Classification of the substance or mixture**



Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms** GHS07
- **Signal word** Warning
- **Hazard statements**
H315 Causes skin irritation.
H319 Causes serious eye irritation.
- **Precautionary statements**
P264 Wash thoroughly after handling.
P280 Wear protective gloves / eye protection / face protection.
P302+P352 If on skin: Wash with plenty of water.
P321 Specific treatment (see on this label).
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P337+P313 If eye irritation persists: Get medical advice/attention.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 0
Reactivity = 0

(Contd. on page 2)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: WAVECALMIX VIS ZODIAC

(Contd. of page 1)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	0	Fire = 0
REACTIVITY	0	Reactivity = 0

· **Other hazards**

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Substances**

· **CAS No. Description**

7732-18-5 Water

· **Identification number(s)**

· **EC number:** 231-791-2










· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Hazardous components:**

7697-37-2	Nitric Acid	 Ox. Liq. 2, H272  Skin Corr. 1A, H314	2.0%
-----------	-------------	---	------

· **Additional Components**

7440-09-7	potassium	 Water-react. 1, H260  Skin Corr. 1B, H314	0.005%
7439-93-2	lithium	 Water-react. 1, H260  Skin Corr. 1B, H314	0.001%
1317-35-7	trimanganese tetraoxide		0.001%
1312-81-8	lanthanum oxide		0.001%
7440-23-5	sodium	 Water-react. 1, H260  Skin Corr. 1B, H314	0.001%
10042-76-9	strontium nitrate	 Ox. Sol. 2, H272	0.001%
7440-70-2	calcium	 Water-react. 2, H261	0.0001%
7440-39-3	barium	 Water-react. 2, H261	0.0001%
7732-18-5	Water		97.9898%

4 First-aid measures

· **Description of first aid measures**

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: WAVECALMIX VIS ZODIAC

(Contd. of page 2)

- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

7697-37-2	Nitric Acid	0.16 ppm
7440-09-7	potassium	2.3 mg/m ³
7439-93-2	lithium	3.3 mg/m ³
1317-35-7	trimanganese tetraoxide	4.2 mg/m ³
1312-81-8	lanthanum oxide	4 mg/m ³
7440-23-5	sodium	13 mg/m ³
10042-76-9	strontium nitrate	5.7 mg/m ³
7440-39-3	barium	1.5 mg/m ³

· PAC-2:

7697-37-2	Nitric Acid	24 ppm
7440-09-7	potassium	25 mg/m ³
7439-93-2	lithium	36 mg/m ³
1317-35-7	trimanganese tetraoxide	6.9 mg/m ³
1312-81-8	lanthanum oxide	44 mg/m ³

(Contd. on page 4)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: WAVECALMIX VIS ZODIAC

(Contd. of page 3)

7440-23-5	sodium	140 mg/m ³
10042-76-9	strontium nitrate	62 mg/m ³
7440-39-3	barium	180 mg/m ³
· PAC-3:		
7697-37-2	Nitric Acid	92 ppm
7440-09-7	potassium	150 mg/m ³
7439-93-2	lithium	220 mg/m ³
1317-35-7	trimanganese tetraoxide	41 mg/m ³
1312-81-8	lanthanum oxide	270 mg/m ³
7440-23-5	sodium	870 mg/m ³
10042-76-9	strontium nitrate	370 mg/m ³
7440-39-3	barium	1,100 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

7697-37-2 Nitric Acid

PEL	Long-term value: 5 mg/m ³ , 2 ppm
REL	Short-term value: 10 mg/m ³ , 4 ppm
	Long-term value: 5 mg/m ³ , 2 ppm
TLV	Short-term value: 10 mg/m ³ , 4 ppm
	Long-term value: 5.2 mg/m ³ , 2 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.

(Contd. on page 5)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: WAVECALMIX VIS ZODIAC

(Contd. of page 4)

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:** Not required.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles or safety glasses

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: Transparent

· **Odor:** Odorless

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: 0 °C (32 °F)

Boiling point/Boiling range: 100 °C (212 °F)

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not applicable.

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

Lower: Not determined.

(Contd. on page 6)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: WAVECALMIX VIS ZODIAC

(Contd. of page 5)

Upper:	<i>Not determined.</i>
· Vapor pressure at 20 °C (68 °F):	<i>23 hPa (17.3 mm Hg)</i>
· Density at 20 °C (68 °F):	<i>1 g/cm³ (8.345 lbs/gal)</i>
· Relative density	<i>Not determined.</i>
· Vapor density	<i>Not determined.</i>
· Evaporation rate	<i>Not determined.</i>
· Solubility in / Miscibility with Water:	<i>Fully miscible.</i>
· Partition coefficient (n-octanol/water):	<i>Not determined.</i>
· Viscosity:	
Dynamic:	<i>Not determined.</i>
Kinematic:	<i>Not determined.</i>
· Solvent content:	
Water:	<i>98.0 %</i>
VOC content:	<i>0.00 %</i>
· Other information	<i>No further relevant information available.</i>

*

10 Stability and reactivity

- **Reactivity** *No further relevant information available.*
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** *No decomposition if used according to specifications.*
- **Possibility of hazardous reactions** *No dangerous reactions known.*
- **Conditions to avoid** *No further relevant information available.*
- **Incompatible materials:** *No further relevant information available.*
- **Hazardous decomposition products:** *No dangerous decomposition products known.*

*

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** *Irritant to skin and mucous membranes.*
- **on the eye:** *Irritating effect.*
- **Sensitization:** *No sensitizing effects known.*
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Carcinogenic categories**
- **IARC (International Agency for Research on Cancer)**
- None of the ingredients is listed.*

(Contd. on page 7)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: WAVECALMIX VIS ZODIAC

(Contd. of page 6)

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:** Not hazardous for water.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Dispose of container and materials in accordance with local, regional and national regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

· **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· **UN-Number**

· **DOT, ADR, IMDG, IATA**

UN3264

· **UN proper shipping name**

· **DOT**

Corrosive liquid, acidic, inorganic, n.o.s.

· **ADR**

3264 Corrosive liquid, acidic, inorganic, n.o.s. (Nitric Acid)

· **IMDG**

CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric Acid),
MARINE POLLUTANT

· **IATA**

CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric Acid)

(Contd. on page 8)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: WAVECALMIX VIS ZODIAC

(Contd. of page 7)

· **Transport hazard class(es)**

· **DOT**



· **Class** 8 Corrosive substances
· **Label** 8

· **ADR**



· **Class** 8 (C1) Corrosive substances
· **Label** 8

· **IMDG**



· **Class** 8 Corrosive substances
· **Label** 8

· **IATA**



· **Class** 8 Corrosive substances
· **Label** 8

· **Packing group**

· **DOT, ADR, IMDG, IATA** III

· **Environmental hazards:**

· **Marine pollutant:** No
Symbol (fish and tree)

· **Special precautions for user**

· **Danger code (Kemler):** Warning: Corrosive substances

· **EMS Number:** 80

· **Segregation groups** F-A, S-B

· **Stowage Category** Acids

· **Stowage Code** A

SW2 Clear of living quarters.

· **Transport in bulk according to Annex II of**

MARPOL73/78 and the IBC Code Not applicable.

(Contd. on page 9)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: WAVECALMIX VIS ZODIAC

(Contd. of page 8)

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations**

On passenger aircraft/rail: 5 L

On cargo aircraft only: 60 L

· **Remarks:**

Special marking with the symbol (fish and tree).

· **ADR**

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **IMDG**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml





Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":**

UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
(NITRIC ACID), 8, III

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

7732-18-5	Water		97.9898%
7697-37-2	Nitric Acid	 Ox. Liq. 2, H272  Skin Corr. 1A, H314	2.0%
7440-09-7	potassium	 Water-react. 1, H260  Skin Corr. 1B, H314	0.005%

· **Sara**

· **Section 355 (extremely hazardous substances):**

7697-37-2	Nitric Acid
-----------	-------------

· **Section 313 (Specific toxic chemical listings):**

7697-37-2	Nitric Acid
1317-35-7	trimanganese tetraoxide
10042-76-9	strontium nitrate
7440-39-3	barium

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

7697-37-2	Nitric Acid
7440-09-7	potassium
7439-93-2	lithium
1317-35-7	trimanganese tetraoxide
1312-81-8	lanthanum oxide
7440-23-5	sodium

(Contd. on page 10)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: WAVECALMIX VIS ZODIAC

(Contd. of page 9)

10042-76-9	strontium nitrate
7440-70-2	calcium
7440-39-3	barium
7732-18-5	Water

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogen categories**

· **EPA (Environmental Protection Agency)**

1317-35-7	trimanganese tetraoxide	D
7440-39-3	barium	D, CBD(inh), NL(oral)

· **TLV (Threshold Limit Value established by ACGIH)**

7440-39-3	barium	A4
-----------	--------	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to this hazardous material. Exceptions can be made by the authorities in certain cases.

· **Water hazard class:** Generally not hazardous for water.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

Disclaimer

The information provided in this Material Safety Data Sheet is based on our present knowledge, and believed to be correct at the date of publication. However, no representation is made concerning its accuracy and completeness. It is intended as guidance only, and is not to be considered a warranty or quality specification. All materials may present unknown hazards, and should be used with caution. Although certain hazards are described, we cannot guarantee that these are the only hazards which exist. PerkinElmer shall not be held liable for any damage resulting from handling or from contact with the product.

· **Department issuing SDS:** Environmental, Health and Safety

· **Contact:**

Within the USA: 1-(800)-762-4000

Outside the USA: 1-(203)-712-8488

(Contd. on page 11)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: WAVECALMIX VIS ZODIAC

(Contd. of page 10)

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Ox. Liq. 2: Oxidizing liquids – Category 2

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

· * Data compared to the previous version altered.

USA

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

1 Identification

- **Product identifier**
- **Trade name:** Optima family vis alignment solution
- **Article number** N0691743
- **Application of the substance / the mixture** Laboratory chemicals
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**

PerkinElmer, Inc.
710 Bridgeport Avenue
Shelton, Connecticut 06484 USA
CustomerCareUS@perkinelmer.com
203-925-4600

- **Emergency telephone number:**
CHEMTREC (within US) 800-424-9300
CHEMTREC (from outside US) +1 703-527-3887 (call collect)
CHEMTREC (within AU) +(61)-290372994

2 Hazard(s) identification

- **Classification of the substance or mixture**
The product is not classified, according to the Globally Harmonized System (GHS).

- **Label elements**
- **GHS label elements** Void
- **Hazard pictograms** Void
- **Signal word** Void
- **Hazard statements** Void
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

HEALTH	0	Health = 0
FIRE	0	Fire = 0
REACTIVITY	0	Reactivity = 0

- **Other hazards**
The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: Optima family vis alignment solution

(Contd. of page 1)




3 Composition/information on ingredients

- **Chemical characterization: Substances**
- **CAS No. Description**
7732-18-5 Water
- **Identification number(s)**
- **EC number: 231-791-2**
- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Hazardous components:**

7647-01-0	Hydrochloric Acid	 Skin Corr. 1B, H314  STOT SE 3, H335	5.0%
-----------	-------------------	--	------

· **Additional Components**

7439-91-0	lanthanum		0.002%
7439-93-2	lithium	 Water-react. 1, H260  Skin Corr. 1B, H314	0.002%
7440-20-2	Scandium from Scandium Oxide		0.002%
7440-70-2	calcium	 Water-react. 2, H261	0.002%
7732-18-5	Water		94.992%

4 First-aid measures

- **Description of first aid measures**
- **General information:** No special measures required.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Inform respective authorities in case of seepage into water course or sewage system.

(Contd. on page 3)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: Optima family vis alignment solution

(Contd. of page 2)

- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

7647-01-0	Hydrochloric Acid	1.8 ppm
7439-91-0	lanthanum	30 mg/m ³
7439-93-2	lithium	3.3 mg/m ³
7440-20-2	Scandium from Scandium Oxide	30 mg/m ³

· **PAC-2:**

7647-01-0	Hydrochloric Acid	22 ppm
7439-91-0	lanthanum	330 mg/m ³
7439-93-2	lithium	36 mg/m ³
7440-20-2	Scandium from Scandium Oxide	330 mg/m ³

· **PAC-3:**

7647-01-0	Hydrochloric Acid	100 ppm
7439-91-0	lanthanum	2,000 mg/m ³
7439-93-2	lithium	220 mg/m ³
7440-20-2	Scandium from Scandium Oxide	2,000 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special measures required.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

7647-01-0 Hydrochloric Acid	
PEL	Ceiling limit value: 7 mg/m ³ , 5 ppm

(Contd. on page 4)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: Optima family vis alignment solution

(Contd. of page 3)

REL	Ceiling limit value: 7 mg/m ³ , 5 ppm
TLV	Ceiling limit value: 2.98 mg/m ³ , 2 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

· **Breathing equipment:** Not required.

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Goggles recommended during refilling.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: Transparent

· **Odor:** Odorless

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: 0 °C (32 °F)

Boiling point/Boiling range: 100 °C (212 °F)

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not applicable.

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

Lower: Not determined.

Upper: Not determined.

· **Vapor pressure at 20 °C (68 °F):** 23 hPa (17.3 mm Hg)

(Contd. on page 5)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: Optima family vis alignment solution

(Contd. of page 4)

- | | |
|---|--|
| · Density at 20 °C (68 °F): | 1 g/cm ³ (8.345 lbs/gal) |
| · Relative density | Not determined. |
| · Vapor density | Not determined. |
| · Evaporation rate | Not determined. |
| · Solubility in / Miscibility with Water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Water: | 95.0 % |
| VOC content: | 0.00 % |
| · Other information | No further relevant information available. |

* **10 Stability and reactivity**

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

* **11 Toxicological information**

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
- The product is not subject to classification according to internally approved calculation methods for preparations.
- When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.
- **Carcinogenic categories**
- **IARC (International Agency for Research on Cancer)**

7647-01-0	Hydrochloric Acid	3
-----------	-------------------	---

- **NTP (National Toxicology Program)**
- None of the ingredients is listed.

(Contd. on page 6)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: Optima family vis alignment solution

(Contd. of page 5)

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.


12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Smaller quantities can be disposed of with household waste.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1789
- **UN proper shipping name**
- **DOT** Hydrochloric acid solution
- **ADR** 1789 Hydrochloric acid solution
- **IMDG, IATA** HYDROCHLORIC ACID solution
- **Transport hazard class(es)**
- **DOT**
- 
- **Class** 8 Corrosive substances

(Contd. on page 7)



acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: Optima family vis alignment solution

(Contd. of page 6)

· Label	8
· ADR	
	
· Class	8 (C1) Corrosive substances
· Label	8
· IMDG, IATA	
	
· Class	8 Corrosive substances
· Label	8
· Packing group	
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Corrosive substances
· Danger code (Kemler):	80
· EMS Number:	F-A,S-B
· Segregation groups	Acids
· Stowage Category	E
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· ADR	
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1789 HYDROCHLORIC ACID SOLUTION, 8, III

USA

(Contd. on page 8)

acc. to OSHA HCS

Printing date 09/19/2018





Review date 09/19/2018

Trade name: Optima family vis alignment solution

(Contd. of page 7)

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

7732-18-5	Water		94.992%
7647-01-0	Hydrochloric Acid	 Skin Corr. 1B, H314  STOT SE 3, H335	5.0%
7439-93-2	lithium	 Water-react. 1, H260  Skin Corr. 1B, H314	0.002%

· Sara

· Section 355 (extremely hazardous substances):

7647-01-0	Hydrochloric Acid
-----------	-------------------

· Section 313 (Specific toxic chemical listings):

7647-01-0	Hydrochloric Acid
-----------	-------------------

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

7647-01-0	Hydrochloric Acid
7439-91-0	lanthanum
7439-93-2	lithium
7440-20-2	Scandium from Scandium Oxide
7440-70-2	calcium
7732-18-5	Water

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

7647-01-0	Hydrochloric Acid	A4
-----------	-------------------	----

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

(Contd. on page 9)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: Optima family vis alignment solution

(Contd. of page 8)

- **National regulations:**
- **Information about limitation of use:**
Workers are not allowed to be exposed to this hazardous material. Exceptions can be made by the authorities in certain cases.
- **Water hazard class:** *Water hazard class 1 (Self-assessment): slightly hazardous for water.*
- **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

Disclaimer

The information provided in this Material Safety Data Sheet is based on our present knowledge, and believed to be correct at the date of publication. However, no representation is made concerning its accuracy and completeness. It is intended as guidance only, and is not to be considered a warranty or quality specification. All materials may present unknown hazards, and should be used with caution. Although certain hazards are described, we cannot guarantee that these are the only hazards which exist. PerkinElmer shall not be held liable for any damage resulting from handling or from contact with the product.

- **Department issuing SDS:** *Environmental, Health and Safety*

· **Contact:**

Within the USA: 1-(800)-762-4000

Outside the USA: 1-(203)-712-8488

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

- *** Data compared to the previous version altered.**

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

1 Identification

- **Product identifier**
- **Trade name:** **MAGNESIUM STRAY LIGHT STANDARD**
- **Article number** N0691745
- **Application of the substance / the mixture** Laboratory chemicals
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**

PerkinElmer, Inc.
710 Bridgeport Avenue
Shelton, Connecticut 06484 USA
CustomerCareUS@perkinelmer.com
203-925-4600

- **Emergency telephone number:**
CHEMTREC (within US) 800-424-9300
CHEMTREC (from outside US) +1 703-527-3887 (call collect)
CHEMTREC (within AU) +(61)-290372994

2 Hazard(s) identification

- **Classification of the substance or mixture**



Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms** GHS05
- **Signal word** Danger

- **Hazard-determining components of labeling:**

Nitric Acid

- **Hazard statements**

H314 Causes severe skin burns and eye damage.

- **Precautionary statements**

P260 Do not breathe dusts or mists.

P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

P321 Specific treatment (see on this label).

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

(Contd. on page 2)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: MAGNESIUM STRAY LIGHT STANDARD

(Contd. of page 1)

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 3

Fire = 0

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 3

Fire = 0

Reactivity = 0

· **Other hazards**

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Substances**

· **CAS No. Description**

7732-18-5 Water

· **Identification number(s)**

· **EC number:** 231-791-2

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Hazardous components:**

7697-37-2	Nitric Acid	Ox. Liq. 2, H272 Skin Corr. 1A, H314	5.0%
7439-95-4	magnesium	Pyr. Sol. 1, H250; Water-react. 1, H260	1.0%

· **Additional Components**

7732-18-5	Water	94.0%
-----------	-------	-------

4 First-aid measures

· **Description of first aid measures**

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: MAGNESIUM STRAY LIGHT STANDARD

(Contd. of page 2)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

7697-37-2	Nitric Acid	0.16 ppm
7439-95-4	magnesium	18 mg/m ³

· PAC-2:

7697-37-2	Nitric Acid	24 ppm
7439-95-4	magnesium	200 mg/m ³

· PAC-3:

7697-37-2	Nitric Acid	92 ppm
7439-95-4	magnesium	1,200 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: MAGNESIUM STRAY LIGHT STANDARD

(Contd. of page 3)

- Prevent formation of aerosols.
- **Information about protection against explosions and fires:** Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

7697-37-2 Nitric Acid

PEL	Long-term value: 5 mg/m ³ , 2 ppm
REL	Short-term value: 10 mg/m ³ , 4 ppm
	Long-term value: 5 mg/m ³ , 2 ppm
TLV	Short-term value: 10 mg/m ³ , 4 ppm
	Long-term value: 5.2 mg/m ³ , 2 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: MAGNESIUM STRAY LIGHT STANDARD

(Contd. of page 4)

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles or safety glasses

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: Transparent

· **Odor:** Odorless

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: 0 °C (32 °F)

Boiling point/Boiling range: 100 °C (212 °F)

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not applicable.

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

Lower: Not determined.

Upper: Not determined.

· **Vapor pressure at 20 °C (68 °F):** 23 hPa (17.3 mm Hg)

· **Density at 20 °C (68 °F):** 1 g/cm³ (8.345 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

Water: Fully miscible.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic: Not determined.

Kinematic: Not determined.

(Contd. on page 6)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: MAGNESIUM STRAY LIGHT STANDARD

(Contd. of page 5)

· Solvent content:	
Water:	94.0 %
VOC content:	0.00 %
· Solids content:	
Other information	1.0 %
	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Caustic effect on skin and mucous membranes.
- **on the eye:**
Strong caustic effect.
Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Corrosive
Irritant
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

USA

(Contd. on page 7)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: MAGNESIUM STRAY LIGHT STANDARD

(Contd. of page 6)

*

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

*

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Dispose of container and materials in accordance with local, regional and national regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

*

14 Transport information

- | | |
|----------------------------------|--|
| · UN-Number | |
| · DOT, ADR, IMDG, IATA | UN3264 |
| · UN proper shipping name | |
| · DOT | Corrosive liquid, acidic, inorganic, n.o.s. (Nitric Acid) |
| · ADR | 3264 Corrosive liquid, acidic, inorganic, n.o.s. (Nitric Acid) |
| · IMDG, IATA | CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric Acid) |

(Contd. on page 8)

USA

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: MAGNESIUM STRAY LIGHT STANDARD

(Contd. of page 7)

· **Transport hazard class(es)**

· **DOT**



· **Class**

8 Corrosive substances

· **ADR, IMDG, IATA**



· **Class**

8 Corrosive substances

· **Packing group**

· **DOT, ADR, IMDG, IATA**

III

· **Environmental hazards:**

· **Marine pollutant:**

No

· **Special precautions for user**

Warning: Corrosive substances

· **Stowage Category**

A

· **Stowage Code**

SW2 Clear of living quarters.

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations**

On passenger aircraft/rail: 5 L

On cargo aircraft only: 60 L

· **ADR**

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **IMDG**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":**

UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID), 8, III

USA

(Contd. on page 9)

acc. to OSHA HCS

Printing date 09/19/2018




Review date 09/19/2018

Trade name: MAGNESIUM STRAY LIGHT STANDARD

(Contd. of page 8)

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

7732-18-5	Water		94.0%
7697-37-2	Nitric Acid	 Ox. Liq. 2, H272  Skin Corr. 1A, H314	5.0%
7439-95-4	magnesium	 Pyr. Sol. 1, H250; Water-react. 1, H260	1.0%

· Sara

· Section 355 (extremely hazardous substances):

7697-37-2	Nitric Acid
-----------	-------------

· Section 313 (Specific toxic chemical listings):

7697-37-2	Nitric Acid
-----------	-------------

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

7697-37-2	Nitric Acid
7439-95-4	magnesium
7732-18-5	Water

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to this hazardous material. Exceptions can be made by the authorities in certain cases.

· Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

(Contd. on page 10)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: MAGNESIUM STRAY LIGHT STANDARD

(Contd. of page 9)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

*

16 Other information

Disclaimer

The information provided in this Material Safety Data Sheet is based on our present knowledge, and believed to be correct at the date of publication. However, no representation is made concerning its accuracy and completeness. It is intended as guidance only, and is not to be considered a warranty or quality specification. All materials may present unknown hazards, and should be used with caution. Although certain hazards are described, we cannot guarantee that these are the only hazards which exist. PerkinElmer shall not be held liable for any damage resulting from handling or from contact with the product.

· **Department issuing SDS:** Environmental, Health and Safety

· Contact:

Within the USA: 1-(800)-762-4000

Outside the USA: 1-(203)-712-8488

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Pyr. Sol. 1: Pyrophoric solids – Category 1

Water-react. 1: Substances and mixtures which in contact with water emit flammable gases – Category 1

Ox. Liq. 2: Oxidizing liquids – Category 2

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

· *** Data compared to the previous version altered.**

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

1 Identification

- **Product identifier**
- **Trade name:** STD ZOD MULTIELEMENT
- **Article number** N0691579
- **Application of the substance / the mixture** Laboratory chemicals
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**

PerkinElmer, Inc.
710 Bridgeport Avenue
Shelton, Connecticut 06484 USA
CustomerCareUS@perkinelmer.com
203-925-4600

- **Emergency telephone number:**
CHEMTREC (within US) 800-424-9300
CHEMTREC (from outside US) +1 703-527-3887 (call collect)
CHEMTREC (within AU) +(61)-290372994

2 Hazard(s) identification

- **Classification of the substance or mixture**



Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms** GHS07
- **Signal word** Warning
- **Hazard statements**
H315 Causes skin irritation.
H319 Causes serious eye irritation.
- **Precautionary statements**
P264 Wash thoroughly after handling.
P280 Wear protective gloves / eye protection / face protection.
P302+P352 If on skin: Wash with plenty of water.
P321 Specific treatment (see on this label).
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P337+P313 If eye irritation persists: Get medical advice/attention.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 0
Reactivity = 0

(Contd. on page 2)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: STD ZOD MULTIELEMENT

(Contd. of page 1)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	0	Fire = 0
REACTIVITY	0	Reactivity = 0

· **Other hazards**

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Substances**

· **CAS No. Description**

7732-18-5 water













· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Hazardous components:**

7697-37-2	Nitric Acid	 Ox. Liq. 2, H272  Skin Corr. 1A, H314	2.0%
-----------	-------------	---	------

· **Additional Components**

7440-09-7	potassium	 Water-react. 1, H260  Skin Corr. 1B, H314	0.005%
7440-38-2	Arsenic	 Acute Tox. 3, H301; Acute Tox. 3, H331  Carc. 1A, H350	0.005%
1317-35-7	trimanganese tetraoxide		0.001%
7440-02-0	nickel	 Carc. 2, H351; STOT RE 1, H372  Skin Sens. 1, H317	0.001%
1312-81-8	lanthanum oxide		0.001%
10042-76-9	strontium nitrate	 Ox. Sol. 2, H272	0.001%
7440-66-6	zinc	 Water-react. 2, H261	0.001%
7439-93-2	lithium	 Water-react. 1, H260  Skin Corr. 1B, H314	0.001%
7439-95-4	magnesium	 Pyr. Sol. 1, H250; Water-react. 1, H260	0.0001%
7440-39-3	barium	 Water-react. 2, H261	0.0001%
7732-18-5	Water		97.9838%

4 First-aid measures

· **Description of first aid measures**

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: STD ZOD MULTIELEMENT

(Contd. of page 2)

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

7697-37-2	Nitric Acid	0.16 ppm
7440-09-7	potassium	2.3 mg/m ³
7440-38-2	Arsenic	1.5 mg/m ³
1317-35-7	trimanganese tetraoxide	4.2 mg/m ³
7440-02-0	nickel	4.5 mg/m ³
1312-81-8	lanthanum oxide	4 mg/m ³
10042-76-9	strontium nitrate	5.7 mg/m ³
7440-66-6	zinc	6 mg/m ³
7439-93-2	lithium	3.3 mg/m ³
7439-95-4	magnesium	18 mg/m ³
7440-39-3	barium	1.5 mg/m ³

· PAC-2:

7697-37-2	Nitric Acid	24 ppm
7440-09-7	potassium	25 mg/m ³

(Contd. on page 4)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: STD ZOD MULTIELEMENT

(Contd. of page 3)

7440-38-2	Arsenic	17 mg/m ³
1317-35-7	trimanganese tetraoxide	6.9 mg/m ³
7440-02-0	nickel	50 mg/m ³
1312-81-8	lanthanum oxide	44 mg/m ³
10042-76-9	strontium nitrate	62 mg/m ³
7440-66-6	zinc	21 mg/m ³
7439-93-2	lithium	36 mg/m ³
7439-95-4	magnesium	200 mg/m ³
7440-39-3	barium	180 mg/m ³

· **PAC-3:**

7697-37-2	Nitric Acid	92 ppm
7440-09-7	potassium	150 mg/m ³
7440-38-2	Arsenic	100 mg/m ³
1317-35-7	trimanganese tetraoxide	41 mg/m ³
7440-02-0	nickel	99 mg/m ³
1312-81-8	lanthanum oxide	270 mg/m ³
10042-76-9	strontium nitrate	370 mg/m ³
7440-66-6	zinc	120 mg/m ³
7439-93-2	lithium	220 mg/m ³
7439-95-4	magnesium	1,200 mg/m ³
7440-39-3	barium	1,100 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:** The product is not flammable.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 5)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: STD ZOD MULTIELEMENT

(Contd. of page 4)

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

7697-37-2 Nitric Acid

PEL	Long-term value: 5 mg/m ³ , 2 ppm
REL	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5 mg/m ³ , 2 ppm
TLV	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5.2 mg/m ³ , 2 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

· **Breathing equipment:** Not required.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles or safety glasses

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Liquid
Color:	Transparent
Odor:	Odorless

(Contd. on page 6)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: STD ZOD MULTIELEMENT

(Contd. of page 5)

· Odor threshold:	<i>Not determined.</i>
· pH-value:	<i>Not determined.</i>
· Change in condition	
Melting point/Melting range:	0 °C (32 °F)
Boiling point/Boiling range:	100 °C (212 °F)
· Flash point:	<i>Not applicable.</i>
· Flammability (solid, gaseous):	<i>Not applicable.</i>
· Decomposition temperature:	<i>Not determined.</i>
· Auto igniting:	<i>Product is not selfigniting.</i>
· Danger of explosion:	<i>Product does not present an explosion hazard.</i>
· Explosion limits:	
Lower:	<i>Not determined.</i>
Upper:	<i>Not determined.</i>
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
· Density at 20 °C (68 °F):	1 g/cm ³ (8.345 lbs/gal)
· Relative density	<i>Not determined.</i>
· Vapor density	<i>Not determined.</i>
· Evaporation rate	<i>Not determined.</i>
· Solubility in / Miscibility with Water:	<i>Fully miscible.</i>
· Partition coefficient (n-octanol/water):	<i>Not determined.</i>
· Viscosity:	
Dynamic:	<i>Not determined.</i>
Kinematic:	<i>Not determined.</i>
· Solvent content:	
Water:	98.0 %
VOC content:	0.00 %
Solids content:	0.1 %
· Other information	<i>No further relevant information available.</i>

10 Stability and reactivity

- **Reactivity** *No further relevant information available.*
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** *No decomposition if used according to specifications.*
- **Possibility of hazardous reactions** *No dangerous reactions known.*
- **Conditions to avoid** *No further relevant information available.*
- **Incompatible materials:** *No further relevant information available.*

(Contd. on page 7)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: STD ZOD MULTIELEMENT

(Contd. of page 6)

· **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **Primary irritant effect:**

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:** Irritating effect.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

7440-38-2	Arsenic	I
7440-02-0	nickel	2B

· **NTP (National Toxicology Program)**

7440-38-2	Arsenic	K
7440-02-0	nickel	R

· **OSHA-Ca (Occupational Safety & Health Administration)**

7440-38-2	Arsenic
-----------	---------

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Dispose of container and materials in accordance with local, regional and national regulations.

(Contd. on page 8)

acc. to OSHA HCS

Printing date 09/19/2018






Review date 09/19/2018

Trade name: STD ZOD MULTIELEMENT

(Contd. of page 7)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· UN-Number	UN3264
· DOT, ADR, IMDG, IATA	
· UN proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s.
· DOT	3264 Corrosive liquid, acidic, inorganic, n.o.s. (Nitric Acid)
· ADR	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric Acid solution)
· IMDG	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric Acid), MARINE POLLUTANT
· IATA	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric Acid)
· Transport hazard class(es)	
· DOT	
	
· Class	8 Corrosive substances
· Label	8
· ADR	
	
· Class	8 (C1) Corrosive substances
· Label	8
· IMDG	
	
· Class	8 Corrosive substances
· Label	8

(Contd. on page 9)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: STD ZOD MULTIELEMENT

(Contd. of page 8)

· IATA



· Class 8 Corrosive substances
· Label 8

· Packing group
· DOT, ADR, IMDG, IATA III

· Environmental hazards:
· Marine pollutant: No
Symbol (fish and tree)

· Special precautions for user Warning: Corrosive substances
· Danger code (Kemler): 80
· EMS Number: F-A,S-B
· Segregation groups Acids
· Stowage Category A
· Stowage Code SW2 Clear of living quarters.

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:
· DOT
· Quantity limitations On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L
· Remarks: Special marking with the symbol (fish and tree).

· ADR
· Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

· IMDG
· Limited quantities (LQ) 5L
· Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID), 8, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

7732-18-5	Water	97.9838%
-----------	-------	----------

(Contd. on page 10)





acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: STD ZOD MULTIELEMENT

(Contd. of page 9)

7697-37-2	Nitric Acid	 Ox. Liq. 2, H272  Skin Corr. 1A, H314	2.0%
7440-38-2	Arsenic	 Acute Tox. 3, H301; Acute Tox. 3, H331  Carc. 1A, H350	0.005%

· Sara

· Section 355 (extremely hazardous substances):

7697-37-2	Nitric Acid
-----------	-------------

· Section 313 (Specific toxic chemical listings):

7697-37-2	Nitric Acid
7440-38-2	Arsenic
1317-35-7	trimanganese tetraoxide
7440-02-0	nickel
10042-76-9	strontium nitrate
7440-66-6	zinc
7440-39-3	barium

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

7697-37-2	Nitric Acid
7440-09-7	potassium
7440-38-2	Arsenic
1317-35-7	trimanganese tetraoxide
7440-02-0	nickel
1312-81-8	lanthanum oxide
10042-76-9	strontium nitrate
7440-66-6	zinc
7439-93-2	lithium
7439-95-4	magnesium
7440-39-3	barium
7732-18-5	Water

· Proposition 65

· Chemicals known to cause cancer:

7440-38-2	Arsenic
7440-02-0	nickel

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 11)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: STD ZOD MULTIELEMENT

(Contd. of page 10)

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

7440-38-2	Arsenic	A
1317-35-7	trimanganese tetraoxide	D
7440-66-6	zinc	D, I, II
7440-39-3	barium	D, CBD(inh), NL(oral)

· **TLV (Threshold Limit Value established by ACGIH)**

7440-38-2	Arsenic	A1
7440-02-0	nickel	A5
7440-39-3	barium	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

7440-38-2	Arsenic	
7440-02-0	nickel	

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to this hazardous material. Exceptions can be made by the authorities in certain cases.

· **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

Disclaimer

The information provided in this Material Safety Data Sheet is based on our present knowledge, and believed to be correct at the date of publication. However, no representation is made concerning its accuracy and completeness. It is intended as guidance only, and is not to be considered a warranty or quality specification. All materials may present unknown hazards, and should be used with caution. Although certain hazards are described, we cannot guarantee that these are the only hazards which exist. PerkinElmer shall not be held liable for any damage resulting from handling or from contact with the product.

· **Department issuing SDS:** Environmental, Health and Safety

· **Contact:**

Within the USA: 1-(800)-762-4000

Outside the USA: 1-(203)-712-8488

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 12)

acc. to OSHA HCS

Printing date 09/19/2018

Review date 09/19/2018

Trade name: STD ZOD MULTIELEMENT

(Contd. of page 11)

NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Ox. Liq. 2: Oxidizing liquids – Category 2
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
· *** Data compared to the previous version altered.**

USA