

Printing date 07/28/2021

Review date 07/28/2021


· Product ident	fier
· Trade name:	STD ZOD-CA STRAY LIGHT
· Article numbe	
• Application of	the substance / the mixture Laboratory chemicals
	supplier of the safety data sheet
· Manufacturer	/Suppuer:
PerkinElmer,	Inc.
710 Bridgepor	
	ecticut 06484 USA
	US@perkinelmer.com
203-925-4600 • Emergency to	lephone number:
	<i>within US)</i> 800-424-9300
	(from outside US) +1 703-527-3887 (call collect)
	within AU) +(61)-290372994
Hazard(s) i	lentification
	·
Classification	of the substance or mixture
FF Cor	rosion
	<i>issues</i>
	H314 Causes severe skin burns and eye damage.
Eye Dam. 1	H318 Causes serious eye damage.
Label element	
	<i>ments</i> The product is classified and labeled according to the Globally Harmonized System (GHS)
• Hazard pictog • Signal word L	
Nitric Acid	nining components of labeling:
· Hazard staten	<i>lents</i>
	severe skin burns and eye damage.
· Precautionary	
P260	Do not breathe dusts or mists.
P264	Wash thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
	P331 If swallowed: Rinse mouth. Do NOT induce vomiting. P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with wat
1 505 1 501 1	shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if prese
	and easy to do. Continue rinsing.
	Immediately call a poison center/doctor.
<i>P310</i>	Specific treatment (see on this label).
P321	
P321 P363	Wash contaminated clothing before reuse.
P321	Wash contaminated clothing before reuse. Store locked up. (Contd. on page



Printing date 07/28/2021

Review date 07/28/2021

Trade name: STD ZOD-CA STRAY LIGHT



4 First-aid measures

• Description of first aid measures

• General information: Immediately remove any clothing soiled by the product.

• After inhalation: In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

• After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

• After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.

· Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)



Printing date 07/28/2021

Review date 07/28/2021

(Contd. of page 2)

Trade name: STD ZOD-CA STRAY LIGHT

• *Indication of any immediate medical attention and special treatment needed No further relevant information available.*

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. • Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
7697-37-2	Nitric Acid	0.16 ppm
· PAC-2:		
7697-37-2	Nitric Acid	24 ppm
· PAC-3:		
7697-37-2	Nitric Acid	92 ppm

7 Handling and storage

• Handling:

- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- Information about protection against explosions and fires: The product is not flammable.
- Keep respiratory protective device available.

(Contd. on page 4)

USA



Printing date 07/28/2021

Review date 07/28/2021

Trade name: STD ZOD-CA STRAY LIGHT

(Contd. of page 3)

· Conditions for safe storage, including any incompatibilities

· Storage:

- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace:
- The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
- At this time, the remaining constituent has no known exposure limits.

7697-37-2 Nitric Acid

- PEL Long-term value: 5 mg/m³, 2 ppm
- *REL* Short-term value: 10 mg/m³, 4 ppm
- Long-term value: 5 mg/m³, 2 ppm
- *TLV* Short-term value: 10 mg/m³, 4 ppm Long-term value: 5.2 mg/m³, 2 ppm

• Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Avoid contact with the eves and skin.
- · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

USA



Printing date 07/28/2021

Review date 07/28/2021

Trade name: STD ZOD-CA STRAY LIGHT

(Contd. of page 4)

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles or safety glasses

9 Physical and chemical properties

General Information		
Appearance:		
Form:	Liquid	
Color:	Transparent	
Odor:	Odorless	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	0 °C (32 °F)	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
J J I	Not determined.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
<i>Density at 20 °C (68 °F):</i>	1 g/cm ³ (8.345 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wate	r): Not determined.	
Viscosity:		
Dynamic:	Not determined.	



Review date 07/28/2021

Trade name: STD ZOD-CA STRAY LIGHT

		(Contd. of page 5)
Kinematic:	Not determined.	
· Solvent content:		
Water:	94.0 %	
VOC content:	0.00 %	
Solids content:	1.0 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

• *Reactivity* No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

- · Acute toxicity:
- · Primary irritant effect:

• on the skin: Caustic effect on skin and mucous membranes.

- \cdot on the eye:
- Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

(Contd. on page 7)

USA



Printing date 07/28/2021

Review date 07/28/2021

Trade name: STD ZOD-CA STRAY LIGHT

(Contd. of page 6)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

• Waste treatment methods

· Recommendation:

Dispose of container and materials in accordance with local, regional and national regulations.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

UN-Number DOT, ADR, IMDG, IATA	UN3264
UN proper shipping name	
• DOT	Corrosive liquid, acidic, inorganic, n.o.s. (nitric acid)
ADR	3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.C.
	(nitric acid)
IMDG, IATA	CORROSÍVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nii
	acid)
Transport hazard class(es)	
DOT	
<u> </u>	
5.34	
CORROSVE	
Class	8 Corrosive substances



F

Printing date 07/28/2021

acc. to OSHA HCS

Review date 07/28/2021

	(Contd. of page
Label	8
ADR	
Class	8 (C1) Corrosive substances
Label	8
IMDG, IATA	
Class	8 Corrosive substances
Label	8
Packing group DOT, ADR, IMDG, IATA	III
Environmental hazards: Marine pollutant:	No
Special precautions for user	Warning: Corrosive substances
Hazard identification number (Kemler code EMS Number:	
EMS Number: Segregation groups	F-A,S-B Acids
Stowage Category	A
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
ADR	
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml



acc. to OSHA HCS

Printing date 07/28/2021

Review date 07/28/2021

(Contd. of page 8)

Trade name: STD ZOD-CA STRAY LIGHT

· UN ''Model Regulation'':

UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID), 8, III

Safety, health and environmental regulations/legislation specific	c for the substance or mixture	
7732-18-5 Water		94.0
7697-37-2 Nitric Acid	Ox. Liq. 2, H272 Skin Corr. 1A, H314	5.0
7440-70-2 calcium	🐼 Water-react. 2, H261	1.0
·Sara		
• Section 355 (extremely hazardous substances):		
7697-37-2 Nitric Acid		
Section 313 (Specific toxic chemical listings):		
7697-37-2 Nitric Acid		
· TSCA (Toxic Substances Control Act):		
All ingredients are listed.		
7732-18-5 Water		ACTIV
7697-37-2 Nitric Acid		ACTIV
7440-70-2 calcium		ACTIV
· Hazardous Air Pollutants		
None of the ingredients is listed.		
· Proposition 65		
· Chemicals known to cause cancer:		
None of the ingredients is listed.		
· Chemicals known to cause reproductive toxicity for females:		
None of the ingredients is listed.		
• Chemicals known to cause reproductive toxicity for males:		
None of the ingredients is listed.		
· Chemicals known to cause developmental toxicity:		
None of the ingredients is listed.		
Cancerogenity categories		
· EPA (Environmental Protection Agency)		
None of the ingredients is listed.		
• TLV (Threshold Limit Value established by ACGIH)		
None of the ingredients is listed.		
None of the ingredients is listed. • NIOSH-Ca (National Institute for Occupational Safety and Hea	ulth)	



Printing date 07/28/2021

Review date 07/28/2021

(Contd. of page 9)

Trade name: STD ZOD-CA STRAY LIGHT

· National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to this hazardous material. Exceptions can be made by the authorities in certain cases.

• Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Disclaimer

The information provided in this Material Safety Data Sheet is based on our present knowledge, and believed to be correct at the date of publication. However, no representation is made concerning its accuracy and completeness. It is intended as guidance only, and is not to be considered a warranty or quality specification. All materials may present unknown hazards, and should be used with caution. Although certain hazards are described, we cannot guarantee that these are the only hazards which exist. PerkinElmer shall not be held liable for any damage resulting from handling or from contact with the product.

· Department issuing SDS: Environmental, Health and Safety

· Contact:

Within the USA: 1-(800)-762-4000 *Outside the USA:* 1-(203)-712-8488

• Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

ADR: Accord europeen sur le transport des marchanaises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Water-react. 2: Substances and mixtures which in contact with water emit flammable gases – Category 2

Ox. Liq. 2: Oxidizing liquids – Category 2

Skin Corr. 1A: Skin corrosion/irritation – Category 1A Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

• * Data compared to the previous version altered.

USA