

Revision: 28.07.2021 Printing date 28.07.2021

Hazardous according to criteria of Australian Safety and Compensation Council.

1 Identification

- · Product identifier
- · Trade name: AltusTM API Calibration Solution
- · Article number: N2972062
- · Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Laboratory chemicals
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

PerkinElmer, Inc. 710 Bridgeport Avenue Shelton, Connecticut 06484 USA CustomerCareUS@perkinelmer.com 203-925-4600

Supplier/Local:

PerkinElmer Australia

Lvl 2, Bldg 5, Brandon Office Park

530-540 Springvale Road

Glen Waverley

Melbourne

VIC 3150

Australia

1-800-033-391

ausales@perkinelmer.com

· Emergency telephone number:

CHEMTREC (within US) 800-424-9300

CHEMTREC (from outside US) +1 703-527-3887 (call collect)

CHEMTREC (within AU) +(61)-290372994

2 Hazard(s) Identification

· Classification of the substance or mixture



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)



Printing date 28.07.2021 Revision: 28.07.2021

Trade name: AltusTM API Calibration Solution

(Contd. of page 1)

- · Label elements
- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms GHS02, GHS07
- · Signal word Danger
- · Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P241 Use explosion-proof electrical/ventilating/lighting equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Other hazards

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous	· Dangerous components:					
67-63-0 pr	opan-2-ol Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	49.995%				
· Additional	Components					
7732-18-5	Water	49.8%				
7681-82-5	sodium iodide	0.2%				
	caesium iodide	0.005%				

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 3)



Printing date 28.07.2021 Revision: 28.07.2021

Trade name: AltusTM API Calibration Solution

(Contd. of page 2)

- · After swallowing: If symptoms persist consult doctor.
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Prevent seepage into sewage system, workpits and cellars.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)



Printing date 28.07.2021 Revision: 28.07.2021

Trade name: AltusTM API Calibration Solution

(Contd. of page 3)

· Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

67-63-0 propan-2-ol

WES Short-term value: 1230 mg/m³, 500 ppm Long-term value: 983 mg/m³, 400 ppm

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

ΑU



Printing date 28.07.2021 Revision: 28.07.2021

Trade name: AltusTM API Calibration Solution

(Contd. of page 4)

Physical and Chemical Propertie	s
· Information on basic physical and chen	nical properties
· General Information	near properties
· Appearance:	
Form:	Liquid
Colour:	Clear
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	2: 82 °C
· Flash point:	13 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	425 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
· Explosion limits:	
Lower:	2 Vol %
Upper:	12 Vol %
· Vapour pressure at 20 °C:	43 hPa
· Density:	Not determined.
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	50.0 %
Water:	49.8 %
Solids content:	0.2 %
· Other information	No further relevant information available.



Printing date 28.07.2021 Revision: 28.07.2021

Trade name: AltusTM API Calibration Solution

(Contd. of page 5)

10 Stability and Reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity
- · Primary irritant effect:
- · Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation Irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological Information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)



Printing date 28.07.2021 Revision: 28.07.2021

Trade name: AltusTM API Calibration Solution

(Contd. of page 6)

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

UN-Number ADG, IMDG, IATA	UN1219
UN proper shipping name ADG IMDG, IATA	1219 ISOPROPANOL (ISOPROPYL ALCOHOL) solutio ISOPROPANOL (ISOPROPYL ALCOHOL) solution
Transport hazard class(es)	
ADG	
Class Label	3 (F1) Flammable liquids. 3
Class Label	3 Flammable liquids. 3
Packing group ADG, IMDG, IATA	II
Environmental hazards: Marine pollutant:	No
Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids. 33 F-E,S-D B
Transport in bulk according to Annex II of Marq and the IBC Code	pol Not applicable.
Transport/Additional information:	
ADG Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport category	2

(Contd. on page 8)



Printing date 28.07.2021 Revision: 28.07.2021

Trade name: AltusTM API Calibration Solution

	(Contd. of page 7)
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2
· Exceptea quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN ''Model Regulation'':	UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL) SOLUTION, 3, II

15 Regulato	Regulatory information Safety, health and environmental regulations/legislation specific for the substance or mixture							
· Safety, hea								
67-63-0	propan-2-ol	Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	49.995%					
7732-18-5	Water		49.8%					
7681-82-5	sodium iodide		0.2%					
· Australia:	Priority Existing Chemicals							
None of the	e ingredients is listed.							

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- · National regulations:
- Information about limitation of use:

Workers are not allowed to be exposed to this hazardous material. Exceptions can be made by the authorities in certain cases.

- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Disclaimer

The information provided in this Material Safety Data Sheet is based on our present knowledge, and believed to be correct at the date of publication. However, no representation is made concerning its accuracy and completeness. It is intended as guidance only, and is not to be considered a warranty or quality specification. All materials may present unknown hazards, and should be used with caution. Although certain hazards are described, we cannot guarantee that these are the only hazards which exist. PerkinElmer Life and Analytical Sciences shall not be held liable for any damage resulting from handling or from contact with the product.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

(Contd. on page 9)



Printing date 28.07.2021 Revision: 28.07.2021

Trade name: AltusTM API Calibration Solution

(Contd. of page 8)

H336 May cause drowsiness or dizziness.

· Department issuing SDS: Environmental, Health and Safety

· Contact:

Within the USA: 1-(800)-762-4000 Outside the USA: 1-(203)-712-8488

· Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* * Data compared to the previous version altered.

AU