

Printing date 07/28/2021 Review date 07/27/2021

1 Identification

- · Product identifier
- · Trade name: Multi-Element Calibration Standard 3
- · Article number N9301720
- · Application of the substance / the mixture Laboratory chemicals
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

PerkinElmer, Inc.

710 Bridgeport Avenue

Shelton, Connecticut 06484 USA

CustomerCareUS@perkinelmer.com

203-925-4600

· Emergency telephone number:

CHEMTREC (within US) 800-424-9300

CHEMTREC (from outside US) +1 703-527-3887 (call collect)

CHEMTREC (within AU) +(61)-290372994

2 Hazard(s) identification

· Classification of the substance or mixture



Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms GHS05
- · Signal word Danger
- · Hazard-determining components of labeling:

Nitric Acid

· Hazard statements

H314 Causes severe skin burns and eye damage.

· Precautionary statements

P260 Do not breathe dusts or mists. P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.
 P321 Specific treatment (see on this label).
 P363 Wash contaminated clothing before reuse.

P405 Store locked up.

(Contd. on page 2)



Printing date 07/28/2021 Review date 07/27/2021

Trade name: Multi-Element Calibration Standard 3

(Contd. of page 1)

P501

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3Fire = 0

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



3 Health = 3Fire = 0

· Other hazards

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· CAS No. Description

7732-18-5 Water

- · EC number: 231-791-2
- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

7697-37-2	Nitric Acid	Ox. Liq. 2, H272 Skin Corr. 1A, H31	5.0%
Additional (Components		
7732-18-5	Water	9	4.971%
1317-35-7	trimanganese tetraoxide	(0.001%
7429-90-5	aluminium	(0.001%
7439-89-6	iron 🕀 Acute Tox. 2, H300		0.001%
7439-92-1	lead		0.001%
7439-93-2	lithium Water-react. 1, H260 Skin Corr. 1B, H314		0.001%
7439-95-4	magnesium Pyr. Sol. 1, H250; Water-react. 1, H260		0.001%
7440-02-0	nickel Carc. 2, H351; STOT RE 1, H372 Skin Sens. 1, H317		0.001%



Printing date 07/28/2021 Review date 07/27/2021

Trade name: Multi-Element Calibration Standard 3

7.440.00.7		(Contd. of pa
7440-09-7	potassium Water-react. 1, H260 Skin Corr. 1B, H314	0.001
7440-17-7	rubidium • Water-react. 1, H260	0.001
	♦ Skin Corr. 1B, H314; Eye Dam. 1, H318	
7440-22-4		0.001
7440-23-5	sodium Water-react. 1, H260 Skin Corr. 1B, H314	0.001
7440-28-0	thallium Acute Tox. 2, H300; Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Chronic 4, H413	0.001
7440-38-2	Arsenic	0.001
7440-39-3	barium Water-react. 2, H261	0.001
7440-41-7		
7440-43-9	V	
7440-46-2	caesium	0.001
7440-47-3	chromium	0.001
7440-48-4		
7440-50-8	copper	0.001
7440-55-3	gallium Skin Corr. 1B, H314	0.001
7440-62-2	vanadium	0.001
7440-66-6	zinc Pyr. Sol. 1, H250; Water-react. 1, H260 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	0.001
7440-69-9	bismuth	0.001

USA



Printing date 07/28/2021 Review date 07/27/2021

Trade name: Multi-Element Calibration Standard 3

		Contd. of page 3
7440-70-2	calcium	0.001%
	♦ Water-react. 2, H261	
7440-74-6	Indium	0.001%
7782-49-2	selenium	0.001%
	Acute Tox. 3, H301; Acute Tox. 3, H331 STOT RE 2, H373 Aquatic Chronic 4, H413	
10042-76-9	strontium nitrate Ox. Sol. 2, H272	0.001%
13520-83-7	uranyl nitrate, hexahydrate Acute Tox. 2, H300; Acute Tox. 2, H330 STOT RE 2, H373	0.001%

4 First-aid measures

- Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system. Dilute with plenty of water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

(Contd. on page 5)



Printing date 07/28/2021 Review date 07/27/2021

Trade name: Multi-Element Calibration Standard 3

(Contd. of page 4)

 ${\it Ensure \ a dequate \ ventilation}.$

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

7697-37-2	Nitric Acid	0.16 ppm
1317-35-7	trimanganese tetraoxide	4.2 mg/m^3
7439-89-6	<u> </u>	3.2 mg/m^3
7439-92-1	lead	0.15 mg/m^3
7439-93-2	lithium	3.3 mg/m^3
7439-95-4	magnesium	18 mg/m³
7440-02-0	nickel	4.5 mg/m^3
7440-09-7		2.3 mg/m^3
7440-17-7	rubidium	3.9 mg/m^3
7440-22-4	silver	0.3 mg/m^3
7440-23-5	sodium	13 mg/m^3
7440-28-0	thallium	0.06 mg/m^3
7440-38-2	Arsenic	1.5 mg/m^3
7440-39-3	barium	1.5 mg/m^3
7440-41-7	beryllium	0.0023 mg/m
7440-43-9	cadmium	0.10 mg/m^3
7440-46-2	caesium	5.6 mg/m^3
7440-47-3	chromium	1.5 mg/m^3
7440-48-4	cobalt	0.18 mg/m^3
7440-50-8	copper	3 mg/m^3
7440-55-3	gallium	30 mg/m^3
7440-62-2	vanadium	$3 mg/m^3$
7440-66-6	zinc	6 mg/m ³
7440-69-9	bismuth	15 mg/m^3
7440-74-6	Indium	0.3 mg/m^3
7782-49-2	selenium	0.6 mg/m^3
10042-76-9	strontium nitrate	5.7 mg/m^3
13520-83-7	uranyl nitrate, hexahydrate	1.3 mg/m^3
PAC-2:		·
7697-37-2	Nitric Acid	24 ppm
1317-35-7	trimanganese tetraoxide	6.9 mg/m^3
7439-89-6		35 mg/m^3
7439-92-1	lead	120 mg/m^3
7439-93-2	lithium	36 mg/m^3



Printing date 07/28/2021 Review date 07/27/2021

Trade name: Multi-Element Calibration Standard 3

7.420.05.4		(Contd. of page
7439-95-4	_	200 mg/m^3
7440-02-0		50 mg/m^3
7440-09-7		25 mg/m ³
7440-17-7		43 mg/m^3
7440-22-4		170 mg/m^3
7440-23-5		140 mg/m^3
7440-28-0		3.3 mg/m^3
7440-38-2	Arsenic	17 mg/m³
7440-39-3		180 mg/m³
7440-41-7	beryllium	0.025 mg/m
7440-43-9	cadmium	$0.76 mg/m^3$
7440-46-2	caesium	61 mg/m³
7440-47-3	chromium	17 mg/m³
7440-48-4	cobalt	$2 mg/m^3$
7440-50-8	copper	33 mg/m^3
7440-55-3	zallium	330 mg/m^3
7440-62-2	<u>'</u> vanadium	5.8 mg/m^3
7440-66-6		21 mg/m³
7440-69-9	bismuth	170 mg/m³
7440-74-6	- Indium	3.3 mg/m^3
7782-49-2		6.6 mg/m^3
	strontium nitrate	62 mg/m^3
	uranyl nitrate, hexahydrate	$7 mg/m^3$
<i>PAC-3:</i>		
7697-37-2	Nitrie Acid	92 ppm
	trimanganese tetraoxide	41 mg/m ³
7439-89-6		$\frac{41 \text{ mg/m}}{150 \text{ mg/m}^3}$
7439-89-0		
		700 mg/m^3
7439-93-2		220 mg/m³
7439-95-4		1,200 mg/m
7440-02-0		99 mg/m³
7440-09-7		150 mg/m^3
7440-17-7		260 mg/m^3
7440-22-4		990 mg/m³
7440-23-5		870 mg/m^3
7440-28-0		20 mg/m^3
7440-38-2		100 mg/m^3
7440-39-3		1,100 mg/m
7440-41-7	beryllium	0.1 mg/m^3
7440-43-9	cadmium	4.7 mg/m^3



Printing date 07/28/2021 Review date 07/27/2021

Trade name: Multi-Element Calibration Standard 3

		(Contd. of page 6)
7440-46-2	caesium	370 mg/m^3
7440-47-3	chromium	99 mg/m³
7440-48-4	cobalt	20 mg/m³
7440-50-8	copper	200 mg/m³
7440-55-3	gallium	$2,000 \text{ mg/m}^3$
7440-62-2	vanadium	35 mg/m ³
7440-66-6	zinc	120 mg/m³
7440-69-9	bismuth	990 mg/m³
7440-74-6	Indium	20 mg/m³
7782-49-2	selenium	40 mg/m³
10042-76-9	strontium nitrate	370 mg/m³
13520-83-7	uranyl nitrate, hexahydrate	42 mg/m³

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

7697-37-2 Nitric Acid

PEL Long-term value: 5 mg/m³, 2 ppm

REL Short-term value: 10 mg/m³, 4 ppm

Long-term value: 5 mg/m³, 2 ppm

TLV Short-term value: 10 mg/m³, 4 ppm

Long-term value: 5.2 mg/m³, 2 ppm

• Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 8)



Printing date 07/28/2021 Review date 07/27/2021

Trade name: Multi-Element Calibration Standard 3

(Contd. of page 7)

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Not determined.

· Eye protection:



Tightly sealed goggles or safety glasses

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid
Color: Transparent
Odor: Characteristic
Odor threshold: Not determined.

· pH-value:

• Change in condition
Melting point/Melting range:
Boiling point/Boiling range:

100 °C (32 °F)
100 °C (212 °F)

• Flash point: Not applicable.

(Contd. on page 9)



Printing date 07/28/2021 Review date 07/27/2021

Trade name: Multi-Element Calibration Standard 3

		(Contd. of page
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard. Not determined.	
Explosion limits: Lower: Upper:	Not determined. Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density at 20 °C (68 °F): Relative density Vapor density Evaporation rate	1 g/cm³ (8.345 lbs/gal) Not determined. Not determined. Not determined.	
Solubility in / Miscibility with Water:	Fully miscible.	
Partition coefficient (n-octanol/wate	e r): Not determined.	
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.	
Solvent content: Water: VOC content:	95.0 % 0.00 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.

(Contd. on page 10)



Printing date 07/28/2021 Review date 07/27/2021

Trade name: Multi-Element Calibration Standard 3

(Contd. of page 9)

on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (Inter	national Agency for Research on Cancer)	
7439-92-1 l	ead	2B
7440-02-0 n	ickel	2B
7440-38-2 A	rsenic	1
7440-41-7 b	eryllium	1
7440-43-9 c	admium	1
7440-47-3 c	hromium	3
7440-48-4 c	obalt	2B
7782-49-2 s	elenium	3
· NTP (Nation	nal Toxicology Program)	
7439-92-1 l	ead	R
7440-02-0 n	ickel	R
7440-38-2 A	rsenic	K
7440-41-7 b	eryllium	K
7440-43-9 c	admium	K
7440-48-4 c	obalt	R
· OSHA-Ca (C	Occupational Safety & Health Administration)	
7440-38-2 A	rsenic	
7440-43-9 c	admium	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · *Mobility in soil* No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

(Contd. on page 11)



Printing date 07/28/2021 Review date 07/27/2021

Trade name: Multi-Element Calibration Standard 3

(Contd. of page 10)

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Dispose of container and materials in accordance with local, regional and national regulations.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

11	T			•	٠
14	Trans	nort	IMT	ormai	i (OM)
	I I WILL	PULL	1,010	OI III	0010

· UN-Number · DOT, ADR, IMDG, IATA	UN3264
· UN proper shipping name	
$\cdot DOT$	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric Acid)
$\cdot ADR$	3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
	(Nitric Acid)
· IMDG, IATA	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric
	Acid)

- · Transport hazard class(es)
- $\cdot DOT$



· Class 8 Corrosive substances

·Label

 \cdot ADR



· Class 8 (C1) Corrosive substances

·Label

(Contd. on page 12)



Printing date 07/28/2021 Review date 07/27/2021

Trade name: Multi-Element Calibration Standard 3

(Contd. of page 11) · IMDG, IATA 8 Corrosive substances · Class ·Label · Packing group · DOT, ADR, IMDG, IATA III· Environmental hazards: · Marine pollutant: No · Special precautions for user Warning: Corrosive substances · Hazard identification number (Kemler code): 80 · EMS Number: F-A,S-B· Segregation groups Acids · Stowage Category · Stowage Code SW2 Clear of living quarters. · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code *Not applicable.* · Transport/Additional information: $\cdot DOT$ · Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L $\cdot ADR$ · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml \cdot IMDG · Limited quantities (LQ) 5L· Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. · UN ''Model Regulation'': (NITRIC ACID), 8, III

Safety, hea	lth and environmental regulations/legislation specific for the sub	stance or mixture	
7732-18-5	Water		94.971%
7697-37-2	Nitric Acid	Ox. Liq. 2, H272 Skin Corr. 1A, H314	5.0%
1317-35-7	trimanganese tetraoxide		0.001%

-USA



Printing date 07/28/2021 Review date 07/27/2021

Trade name: Multi-Element Calibration Standard 3

	(Contd. of page
· Sara · Section 355 (extremely hazardous substances):	
7697-37-2 Nitric Acid	
Section 313 (Specific toxic chemical listings):	
7697-37-2 Nitric Acid	
1317-35-7 trimanganese tetraoxide	
7429-90-5 aluminium	
7439-92-1 lead	
7440-02-0 nickel	
7440-22-4 silver	
7440-28-0 thallium	
7440-38-2 Arsenic	
7440-39-3 barium	
7440-41-7 beryllium	
7440-43-9 cadmium	
7440-47-3 chromium	
7440-48-4 cobalt	
7440-50-8 copper	
7440-62-2 vanadium	
7440-66-6 zinc	
7782-49-2 selenium	
10042-76-9 strontium nitrate	
TSCA (Toxic Substances Control Act): All ingredients are listed.	
7732-18-5 Water	ACTIV
7697-37-2 Nitric Acid	ACTIV
1317-35-7 trimanganese tetraoxide	ACTIV
7429-90-5 aluminium	ACTIV
7439-89-6 iron	ACTIV
7439-92-1 lead	ACTIV
7439-93-2 lithium	ACTIV
7439-95-4 magnesium	ACTIV
7440-02-0 nickel	ACTIV
7440-09-7 potassium	ACTIV
7440-17-7 rubidium	ACTIV
7440-22-4 silver	ACTIV
7440-23-5 sodium	ACTIV
7440-28-0 thallium	ACTIV
	ACTIV
7440-38-2 Arsenic	ACTIV



Printing date 07/28/2021 Review date 07/27/2021

Trade name: Multi-Element Calibration Standard 3

		(Contd. of page
7440-41-7	beryllium	ACTIV
7440-43-9	cadmium	ACTIV
7440-46-2	caesium	ACTIV
7440-47-3	chromium	ACTIV
7440-48-4	cobalt	ACTIV
7440-50-8	copper	ACTIV
7440-55-3	gallium	ACTIV
7440-62-2	vanadium	ACTIV
7440-66-6	zinc	ACTIV
7440-69-9	bismuth	ACTIV
7440-70-2	calcium	ACTIV
7440-74-6	Indium	ACTIV
7782-49-2	selenium	ACTIV
10042-76-9	strontium nitrate	ACTIV
· Hazardous A	Air Pollutants	
1317-35-7 t	rimanganese tetraoxide	
7439-92-1 l	ead	
7440-48-4	cobalt	
·Proposition	65	
· Chemicals k	nown to cause cancer:	
7439-92-1 l	ead	
7440-02-0 1	nickel	
7440-38-2	Arsenic	
7440-41-7	peryllium	
7440-43-9	eadmium	
7440-48-4	eobalt	
· Chemicals k	nown to cause reproductive toxicity for females:	
7439-92-1 l	ead	
· Chemicals k	nown to cause reproductive toxicity for males:	
7439-92-1 l	ead	
7440-43-9	cadmium	
· Chemicals k	nown to cause developmental toxicity:	
7439-92-1 l	<u> </u>	
7440-43-9	cadmium	
· Cancerosen	ity categories	
	onmental Protection Agency)	
**	rimanganese tetraoxide	D
7439-92-1	_	B2
		D
7440-22-4 s	liver	D



Printing date 07/28/2021 Review date 07/27/2021

Trade name: Multi-Element Calibration Standard 3

		(Contd. of page 1
7440-38-2		A
7440-39-3	barium	D, CBD(inh), NL(oral)
7440-41-7	beryllium	B1, K/L(inh), CBD(oral
7440-43-9	cadmium	B1
7440-47-3	chromium	D
7440-50-8	copper	D
7440-66-6	zinc	D, I, II
7782-49-2	selenium	D
· TLV (Thres	hold Limit Value established by ACGIH)	
7429-90-5	aluminium	A
7439-92-1	lead	A
7440-02-0	nickel	A
7440-38-2	Arsenic	A
7440-39-3	barium	A
7440-41-7	beryllium	A
7440-43-9	cadmium	A
7440-47-3	chromium	A
7440-48-4	cobalt	A
13520-83-7	uranyl nitrate, hexahydrate	A
· NIOSH-Ca	(National Institute for Occupational Safety and Health)	
7440-02-0	nickel	
7440-38-2	Arsenic	
7440-41-7	beryllium	
7440-43-9	cadmium	
13520-83-7	uranyl nitrate, hexahydrate	

- · National regulations:
- · Information about limitation of use:

Workers are not allowed to be exposed to this hazardous material. Exceptions can be made by the authorities in certain cases.

- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Disclaimer

The information provided in this Material Safety Data Sheet is based on our present knowledge, and believed to be correct at the date of publication. However, no representation is made concerning its accuracy and completeness. It is intended as guidance only, and is not to be considered a warranty or quality specification. All materials may present unknown hazards, and should be used with caution. Although certain hazards are described, we cannot guarantee that these are the only hazards which exist. PerkinElmer shall not be held liable for any damage resulting from handling or from contact with the product.

(Contd. on page 16)



Review date 07/27/2021 Printing date 07/28/2021

Trade name: Multi-Element Calibration Standard 3

(Contd. of page 15)

· Department issuing SDS: Environmental, Health and Safety

· Contact:

Within the USA: 1-(800)-762-4000 Outside the USA: 1-(203)-712-8488

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Ox. Liq. 2: Oxidizing liquids - Category 2

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

* Data compared to the previous version altered.