

Printing date 03/29/2021 Review date 03/29/2021

## 1 Identification

- · Product identifier
- · Trade name: Instrument Calibration Standard 2
- · Article number N9301721
- · Application of the substance / the mixture Laboratory chemicals
- Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

PerkinElmer, Inc.

710 Bridgeport Avenue

Shelton, Connecticut 06484 USA

CustomerCareUS@perkinelmer.com

203-925-4600

· Emergency telephone number:

CHEMTREC (within US) 800-424-9300

CHEMTREC (from outside US) +1 703-527-3887 (call collect)

CHEMTREC (within AU) +(61)-290372994

## 2 Hazard(s) identification

· Classification of the substance or mixture



Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms GHS05, GHS07
- · Signal word Danger
- · Hazard-determining components of labeling:

Nitric Acid

Hydrofluoric acid

· Hazard statements

H302+H312 Harmful if swallowed or in contact with skin. H314 Causes severe skin burns and eye damage.

· Precautionary statements

P260 Do not breathe dusts or mists. P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P312 If swallowed: Call a poison center/doctor if you feel unwell.

(Contd. on page 2)



Printing date 03/29/2021 Review date 03/29/2021

#### Trade name: Instrument Calibration Standard 2

(Contd. of page 1)

*P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.* 

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor. P321 Specific treatment (see on this label).

*P362+P364* Take off contaminated clothing and wash it before reuse.

*P363* Wash contaminated clothing before reuse.

*P405* Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 3 Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



3 Health = 30 Fire = 0

REACTIVITY 0 Reactivity = 0

· Other hazards

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Hazardous	components:	
	Nitric Acid	5.0%
	Ox. Liq. 2, H272 Skin Corr. 1A, H314	
	Hydrofluoric acid	0.3%
	Acute Tox. 2, H300; Acute Tox. 1, H310; Acute Tox. 2, H330 Skin Corr. 1A, H314	

### · Additional Components

7732-18-5 Water 94.474%

(Contd. on page 3)



Printing date 03/29/2021 Review date 03/29/2021

133-37-0	(+-)-tartaric acid	(Contd. of pa
	molybdenum trioxide	0.27
1313-2/-3	Acute Tox. 3, H301	
	& Carc. 2, H351	
	Eye Irrit. 2A, H319; STOT SE 3, H335	
1317-35-7	trimanganese tetraoxide	0.001
7429-90-5	aluminium	0.001
7439-89-6	iron	0.001
	♠ Acute Tox. 2, H300	
7439-92-1	lead	0.001
	🗞 Carc. 2, H351; Repr. 1A, H360	
7439-95-4	magnesium	0.001
	📀 Pyr. Sol. 1, H250; Water-react. 1, H260	
7440-02-0		0.00
	© Carc. 2, H351; STOT RE 1, H372	
7440.00.7	Skin Sens. 1, H317	0.00
7440-09-7	potassium  Water-react. 1, H260	0.00
	Water-react. 1, H200 Skin Corr. 1B, H314	
7440-22-4		0.00
7440-23-5		0.00
, , , , 0 23 5	<b>♦</b> Water-react. 1, H260	
	Skin Corr. 1B, H314	
7440-28-0	thallium	0.00
	Acute Tox. 2, H300; Acute Tox. 2, H330	
	<b>♦</b> STOT RE 2, H373	
7440 21 5	Aquatic Chronic 4, H413	0.00
7440-31-5		0.00
7440-32-6	L	0.00
7440 26 0	♦ Self-heat. 1, H251; Water-react. 1, H260	0.00
7440-36-0	<i>anumony</i> ♠ Acute Tox. 3, H311; Acute Tox. 3, H331	
7440-38-2	· ·	0.00
7440-30-2	Acute Tox. 3, H301; Acute Tox. 3, H331	
	& Carc. 1A, H350	
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
7440-39-3	barium	0.00
	🔷 Water-react. 2, H261	
7440-41-7		0.001
	Acute Tox. 3, H301; Acute Tox. 2, H330	
	© Carc. 1B, H350; STOT RE 1, H372 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	
7440-43-9	·	0.001
/440-43-9	Caamium  ♠ Acute Tox. 3, H301; Acute Tox. 2, H330	
	<b>№</b> Muta. 2, H341; Carc. 1B, H350; Repr. 2, H361; STOT RE 1, H372	
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	



Printing date 03/29/2021 Review date 03/29/2021

#### Trade name: Instrument Calibration Standard 2

		(Contd. of page
7440-47-3	chromium	0.001%
7440-48-4	cobalt  Resp. Sens. 1, H334; Carc. 2, H351 Skin Sens. 1, H317 Aquatic Chronic 4, H413	0.001%
7440-50-8	copper	0.001%
7440-62-2	vanadium	0.001%
7440-66-6	zinc      Water-react. 2, H261     Aquatic Chronic 1, H410  Aquatic Acute 2, H401	0.001%
7440-70-2	calcium Water-react. 2, H261	0.001%
7782-49-2	selenium Acute Tox. 3, H301; Acute Tox. 3, H331 STOT RE 2, H373 Aquatic Chronic 4, H413	0.001%
10042-76-9	strontium nitrate  Ox. Sol. 2, H272	0.001%

## 4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact:

*Immediately wash with water and soap and rinse thoroughly.* 

Rub in Ca-gluconate solution or Ca-gluconate gel immediately.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

# 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

(Contd. on page 5)



Printing date 03/29/2021 Review date 03/29/2021

Trade name: Instrument Calibration Standard 2

(Contd. of page 4)

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

## 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

PAC-1: 7697-37-2	Nituia Aaid	0.16 nam
		0.16 ppm
	molybdenum trioxide	$2.3 \text{ mg/m}^3$
1317-35-7	trimanganese tetraoxide	$4.2 \text{ mg/m}^3$
7439-89-6	iron	3.2 mg/m <sup>3</sup>
7439-92-1	lead	$0.15 \text{ mg/m}^3$
7439-95-4	magnesium	18 mg/m³
7440-02-0	nickel	$4.5 \text{ mg/m}^3$
7440-09-7	potassium	$2.3 \text{ mg/m}^3$
7440-22-4	silver	$0.3 \text{ mg/m}^3$
7440-23-5	sodium	13 mg/m³
7440-28-0	thallium	$0.06 \text{ mg/m}^3$
7440-31-5	tin	6 mg/m <sup>3</sup>
7440-32-6	titanium	30 mg/m³
7440-36-0	antimony	$1.5 \text{ mg/m}^3$
7440-38-2	Arsenic	$1.5 \text{ mg/m}^3$
7440-39-3	barium	$1.5 \text{ mg/m}^3$
7440-41-7	beryllium	0.0023 mg/m
7440-43-9	cadmium	$0.10 \text{ mg/m}^3$
7440-47-3	chromium	$1.5 \text{ mg/m}^3$
7440-48-4	cobalt	$0.18 \text{ mg/m}^3$
7440-50-8	copper	$3 mg/m^3$
		(Contd. on page

USA



Printing date 03/29/2021 Review date 03/29/2021

		(Contd. of page
7440-62-2	vanadium	$3 \text{ mg/m}^3$
7440-66-6	zinc	$6 mg/m^3$
7782-49-2	selenium	$0.6 \text{ mg/m}^3$
10042-76-9	strontium nitrate	$5.7 \text{ mg/m}^3$
· PAC-2:		
7697-37-2	Nitric Acid	24 ppm
1313-27-5	molybdenum trioxide	$43 \text{ mg/m}^3$
	trimanganese tetraoxide	$6.9 \text{ mg/m}^3$
7439-89-6		$35 \text{ mg/m}^3$
7439-92-1	lead	120 mg/m³
7439-95-4	magnesium	$200 \text{ mg/m}^3$
7440-02-0		$50 \text{ mg/m}^3$
7440-09-7	potassium	$25 \text{ mg/m}^3$
7440-22-4	*	$170 \text{ mg/m}^3$
7440-23-5	sodium	$140 \text{ mg/m}^3$
7440-28-0	thallium	$3.3 \text{ mg/m}^3$
7440-31-5	tin	$67 \text{ mg/m}^3$
7440-32-6	titanium	$330 \text{ mg/m}^3$
7440-36-0	antimony	13 mg/m³
7440-38-2	Arsenic	$17 \text{ mg/m}^3$
7440-39-3	barium	180 mg/m³
7440-41-7	beryllium	0.025 mg/n
7440-43-9	cadmium	0.76 mg/m <sup>2</sup>
7440-47-3	chromium	$17 \text{ mg/m}^3$
7440-48-4	cobalt	2 mg/m <sup>3</sup>
7440-50-8	copper	$33 \text{ mg/m}^3$
7440-62-2	vanadium	$5.8 \text{ mg/m}^3$
7440-66-6	zinc	$21 \text{ mg/m}^3$
7782-49-2	selenium	6.6 mg/m³
10042-76-9	strontium nitrate	$62 \text{ mg/m}^3$
· PAC-3:		
7697-37-2	Nitric Acid	92 ppm
1313-27-5	molybdenum trioxide	$260 \text{ mg/m}^3$
	trimanganese tetraoxide	$41 \text{ mg/m}^3$
7439-89-6	iron	150 mg/m <sup>3</sup>
7439-92-1	lead	700 mg/m³
7439-95-4	magnesium	1,200 mg/n
7440-02-0	nickel	99 mg/m³
7440-09-7	potassium	150 mg/m³
7440-22-4	silver	990 mg/m³



Printing date 03/29/2021 Review date 03/29/2021

#### Trade name: Instrument Calibration Standard 2

7440-23-5	sodium	(Contd. of page of 870 mg/m <sup>3</sup>
7440-23-3		$\frac{370 \text{ mg/m}}{20 \text{ mg/m}^3}$
7440-31-5		$400 \text{ mg/m}^3$
7440-32-6	titanium	2,000 mg/m <sup>2</sup>
7440-36-0	antimony	$80 \text{ mg/m}^3$
7440-38-2	Arsenic	$100 \text{ mg/m}^3$
7440-39-3	barium	$1,100 \text{ mg/m}^{2}$
7440-41-7	beryllium	$0.1 \text{ mg/m}^{3}$
7440-43-9	cadmium	$4.7 \text{ mg/m}^3$
7440-47-3	chromium	99 mg/m³
7440-48-4	cobalt	$20 \text{ mg/m}^3$
7440-50-8	copper	$200 \text{ mg/m}^3$
7440-62-2	vanadium	35 mg/m <sup>3</sup>
7440-66-6	zinc	$120 \text{ mg/m}^3$
7782-49-2	selenium	$40 \text{ mg/m}^3$
10042-76-9	strontium nitrate	$370 \text{ mg/m}^3$

# 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

	· Components with	limit values th	hat require moni	toring at ti	he workplace.
--	-------------------	-----------------	------------------	--------------	---------------

### 7697-37-2 Nitric Acid

PEL Long-term value: 5 mg/m³, 2 ppm
REL Short-term value: 10 mg/m³, 4 ppm
Long-term value: 5 mg/m³, 2 ppm

(Contd. on page 8)



Printing date 03/29/2021 Review date 03/29/2021

Trade name: Instrument Calibration Standard 2

(Contd. of page 7)

TLV Short-term value: 10 mg/m³, 4 ppm Long-term value: 5.2 mg/m³, 2 ppm

### 7664-39-3 Hydrofluoric acid

PEL Long-term value: 1\* mg/m³, 3 ppm

as F, \*sulfuric acid

REL Long-term value: 2.5 mg/m³, 3 ppm Ceiling limit value: 5\* mg/m³, 6\* ppm

\*15-min, as F

TLV Long-term value: 0.41 mg/m³, 0.5 ppm Ceiling limit value: 1.64 mg/m³, 2 ppm

as F; Skin; BEI

### · Ingredients with biological limit values:

#### 7664-39-3 Hydrofluoric acid

BEI 3 mg/g creatinine

Medium: urine Time: prior to shift

Parameter: Flourides (background)

10 mg/g creatinine Medium: urine Time: end of shift

Parameter: Flourides (background)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 9)



Printing date 03/29/2021 Review date 03/29/2021

Trade name: Instrument Calibration Standard 2

(Contd. of page 8)

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles or safety glasses

Information on basic physical and c	hemical properties	
General Information	F. of contrast	
Appearance:		
Form:	Liquid	
Color:	Transparent	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value at 20 °C (68 °F):	<4	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
3 7 1	Not determined.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density at 20 °C (68 °F):	1 g/cm³ (8.345 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/wate	r): Not determined.	
Viscosity:		
Dynamic:	Not determined.	



Printing date 03/29/2021 Review date 03/29/2021

Trade name: Instrument Calibration Standard 2

		(Contd. of page 9)
Kinematic:	Not determined.	
· Solvent content:		
Water:	94.5 %	
VOC content:	0.00 %	
• Other information No further relevant information available.		

# 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

# 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

2B
2B
2B
1
1
1
3
2B

(Contd. on page 11)



Printing date 03/29/2021 Review date 03/29/2021

Trade name: Instrument Calibration Standard 2

7702 (0.2	(Cont	d. of page 10)
7782-49-2	selenium	3
· NTP (Nati	ional Toxicology Program)	
7439-92-1	lead	R
7440-02-0	nickel	R
7440-38-2	Arsenic	K
7440-41-7	beryllium	K
7440-43-9	cadmium	K
7440-48-4	cobalt	R
· OSHA-Ca	(Occupational Safety & Health Administration)	
7440-38-2	Arsenic	
7440-43-9	cadmium	

# 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

# 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Dispose of container and materials in accordance with local, regional and national regulations.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

## 14 Transport information

- · UN-Number
- · DOT, ADR, IMDG, IATA UN3264

(Contd. on page 12)



Printing date 03/29/2021 Review date 03/29/2021

	(Contd. of page
UN proper shipping name	
DOT	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric Ac
ADR	hydrofluoric acid) 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O
	(Nitric Acid, hydrofluoric acid)
IMDG	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nit. Acid, hydrofluoric acid), MARINE POLLUTANT
IATA	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nit.
	Acid, hydrofluoric acid)
Transport hazard class(es)	
DOT	
CORROSOVE Y	
Class Label	8 Corrosive substances 8
ADR	
<u> </u>	
Class Label	8 (C1) Corrosive substances 8
IMDG	<del>-</del>
¥2>	
Class	8 Corrosive substances
Label	8
IATA	
Class	8 Corrosive substances
Label	8
Packing group DOT, ADR, IMDG, IATA	III
Environmental hazards:	
Marine pollutant:	No
	Symbol (fish and tree)



Printing date 03/29/2021 Review date 03/29/2021

Trade name: Instrument Calibration Standard 2

	(Contd. of page
Special precautions for user	Warning: Corrosive substances
Hazard identification number (Kemler co	de): 80
EMS Number:	F- $A$ , $S$ - $B$
Segregation groups	Acids
· Stowage Category	A
· Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex II	of
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
·DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
· Remarks:	Special marking with the symbol (fish and tree).
· <i>ADR</i>	
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ)	5L
Excepted quantities $(EQ)$	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.
J	(NITRIC ACID, HYDROFLUORIC ACID), 8, III

· Safety, health and environmental regulations/legislation specific for the substance or mixture				
7732-18-5	Water	94.474%		
7697-37-2	Nitric Acid	5.0%		
	© Ox. Liq. 2, H272 Skin Corr. 1A, H314			
7664-39-3	Hydrofluoric acid	0.3%		
	Acute Tox. 2, H300; Acute Tox. 1, H310; Acute Tox. 2, H330 Skin Corr. 1A, H314			
Sara		·		
Section 35	5 (extremely hazardous substances):			
7697-37-2	Nitric Acid			
Section 31	3 (Specific toxic chemical listings):			
7697-37	2 Nitric Acid			
1313-27	5 molybdenum trioxide			
1317-35-	7 trimanganese tetraoxide			

USA



Printing date 03/29/2021 Review date 03/29/2021

	(Contd. of page
7429-90-5 aluminium	(
7439-92-1 lead	
7440-02-0 nickel	
7440-22-4 silver	
7440-28-0 thallium	
7440-36-0 antimony	
7440-38-2 Arsenic	
7440-39-3 barium	
7440-41-7 beryllium	
7440-43-9 cadmium	
7440-47-3 chromium	
7440-48-4 cobalt	
7440-50-8 copper	
7440-62-2 vanadium	
7440-66-6 zinc	
7782-49-2 selenium	
10042-76-9 strontium nitrate	
· TSCA (Toxic Substances Control Act):	
All ingredients are listed.	
7732-18-5   Water	ACTIV.
7697-37-2 Nitric Acid	ACTIV
133-37-9 (+-)-tartaric acid	ACTIV
1313-27-5 molybdenum trioxide	ACTIV
1317-35-7 trimanganese tetraoxide	ACTIV
7429-90-5 aluminium	ACTIV
7439-89-6 iron	ACTIV
7439-92-1 lead	ACTIV
7439-95-4 magnesium	ACTIV
7440-02-0 nickel	ACTIV
7440-09-7 potassium	ACTIV
7440-22-4 silver	ACTIV
7440-23-5 sodium	ACTIV
7440-28-0 thallium	ACTIV
7440-31-5 tin	ACTIV
7440-32-6 titanium	ACTIV
7440-36-0 antimony	ACTIV.
7440-38-2 Arsenic	ACTIV
7440-39-3 barium	ACTIV
7440-41-7 beryllium	ACTIV.
the state of the s	ACTIV



Printing date 03/29/2021 Review date 03/29/2021

		(Contd. of page 1		
7440-47-3 chromium		ACTIVI		
7440-48-4 cobalt		ACTIVI		
7440-50-8 copper		ACTIVI		
7440-62-2 vanadium		ACTIVI		
7440-66-6 zinc		ACTIVI		
7440-70-2 calcium		ACTIVI		
7782-49-2 selenium		ACTIV		
10042-76-9 strontium nitrate		ACTIV		
Hazardous	Air Pollutants			
1317-35-7	trimanganese tetraoxide			
7439-92-1	lead			
7440-48-4	cobalt			
Proposition	65			
Chemicals I	known to cause cancer:			
7439-92-1	7439-92-1   lead			
7440-02-0	nickel			
7440-38-2	Arsenic			
7440-41-7	beryllium			
7440-43-9	cadmium			
7440-48-4	cobalt			
Chemicals I	known to cause reproductive toxicity for females:			
7439-92-1	lead			
Chemicals I	known to cause reproductive toxicity for males:			
7439-92-1	-			
7440-43-9	cadmium			
Chemicals 1	known to cause developmental toxicity:			
7439-92-1				
7440-43-9				
	ity categories			
	conmental Protection Agency)			
	trimanganese tetraoxide	D		
7439-92-1		B2		
7440-22-4		D		
7440-38-2		A		
7440-39-3		D, CBD(inh), NL(oral)		
7440-41-7		B1, K/L(inh), CBD(ora		
7440-43-9		B1		
7440-47-3		D		
= 4 40 = 0	copper	D		



Printing date 03/29/2021 Review date 03/29/2021

Trade name: Instrument Calibration Standard 2

			(Contd. of page 15
7440-66-6	zinc	D, I, II	
7782-49-2	selenium	D	
· TLV (Thre	shold Limit Value established by ACGIH)		
7429-90-5	aluminium		A4
7439-92-1	lead		A3
7440-02-0	nickel		A5
7440-38-2	Arsenic		A1
7440-39-3	barium		A4
7440-41-7	beryllium		A1
7440-43-9	cadmium		A2
7440-47-3	chromium		A4
7440-48-4	cobalt		<i>A3</i>
· NIOSH-Ca	(National Institute for Occupational Safety and Health)		
7440-02-0	nickel		
7440-38-2	Arsenic		
7440-41-7	beryllium		
7440-43-9	cadmium		

- · National regulations:
- · Information about limitation of use:

Workers are not allowed to be exposed to this hazardous material. Exceptions can be made by the authorities in certain cases.

- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# 16 Other information

Disclaimer

The information provided in this Material Safety Data Sheet is based on our present knowledge, and believed to be correct at the date of publication. However, no representation is made concerning its accuracy and completeness. It is intended as guidance only, and is not to be considered a warranty or quality specification. All materials may present unknown hazards, and should be used with caution. Although certain hazards are described, we cannot guarantee that these are the only hazards which exist. PerkinElmer shall not be held liable for any damage resulting from handling or from contact with the product.

- · Department issuing SDS: Environmental, Health and Safety
- · Contact:

Within the USA: 1-(800)-762-4000 Outside the USA: 1-(203)-712-8488

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 17)



Printing date 03/29/2021 Review date 03/29/2021

#### Trade name: Instrument Calibration Standard 2

(Contd. of page 16)

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Ox. Liq. 2: Oxidizing liquids - Category 2

Acute Tox. 2: Acute toxicity – Category 2 Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 1: Acute toxicity – Category 1

Skin Corr. 1A: Skin corrosion/irritation - Category 1A

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Čategory 1

<sup>\* \*</sup> Data compared to the previous version altered.