

Printing date 25.03.2019 Revision: 25.03.2019

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: STD-NICKEL 5% HNO3 10000 MG/L
- · Article number: N9304117
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Laboratory chemicals
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

PerkinElmer, Inc.

710 Bridgeport Avenue

Shelton, Connecticut 06484 USA

CustomerCareUS@perkinelmer.com

203-925-4600

PerkinElmer, Inc.

Chalfont Road Buckinghamshire

Seer Green HP9 2FX

cc.uk@perkinelmer.com

United Kingdom

P: 0800 896 046

F: 0800-89 17 14

PerkinElmer, Inc.

Llantrisant Business Park, Unit A

Llantrisant CF72 8YW

United Kingdom

cc.uk@perkinelmer.com

P: 44 1443 234005

· 1.4 Emergency telephone number:

CHEMTREC (within US) 800-424-9300

CHEMTREC (from outside US) +1 703-527-3887 (call collect)

CHEMTREC (within AU) +(61)-290372994

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

(Contd. on page 2)



Printing date 25.03.2019 Revision: 25.03.2019

Trade name: STD-NICKEL 5% HNO3 10000 MG/L

(Contd. of page 1)



Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms GHS05, GHS07, GHS08
- · Signal word Danger

#### · Hazard-determining components of labelling:

Nitric Acid

nickel

#### · Hazard statements

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

#### · Precautionary statements

*P260* Do not breathe dusts or mists.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

*P362+P364* Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · 2.3 Other hazards

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dar	· Dangerous components:					
0110	S: 7697-37-2 VECS: 231-714-2	Nitric Acid	<ul><li>Ox. Liq. 2, H272</li><li>Skin Corr. 1A, H314</li></ul>	5.0%		
	S: 7440-02-0 /ECS: 231-111-4	nickel	© Carc. 2, H351; STOT RE 1, H372 Skin Sens. 1, H317	1.0%		
			(Contd. or			

(Contd. on page 3)



Printing date 25.03.2019 Revision: 25.03.2019

Trade name: STD-NICKEL 5% HNO3 10000 MG/L

(Contd. of page 2)

· Additional Components			
CAS: 7732-18-5	Water	94.0%	
EINECS: 231-791-2			

· Additional information: For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

*Inform respective authorities in case of seepage into water course or sewage system.* 

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

*Use neutralising agent.* 

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)



Printing date 25.03.2019 Revision: 25.03.2019

Trade name: STD-NICKEL 5% HNO3 10000 MG/L

(Contd. of page 3)

See Section 13 for disposal information.

## SECTION 7: Handling and storage

#### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

- Information about fire and explosion protection: Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

7697-37-2 Nitric Acid

WEL Short-term value: 2.6 mg/m³, 1 ppm

#### 7440-02-0 nickel

WEL Long-term value: 0.5 mg/m<sup>3</sup>

as Ni; Sk; Carc

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)



Printing date 25.03.2019 Revision: 25.03.2019

Trade name: STD-NICKEL 5% HNO3 10000 MG/L

(Contd. of page 4)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9:	Physical and	l chemical	properties
------------	--------------	------------	------------

9.1 Information on basic physical and ch	namical proparties
General Information	iemicui properties
· Appearance:	
Form:	Liquid
Colour:	Clear
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	100 °C
· Flash point:	Not applicable.
· Flammability (solid, gas):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
	Not determined.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure at 20 °C:	23 hPa
· Density:	Not determined.
· Relative density	Not determined.
· Vapour density	Not determined.
Evaporation rate	Not determined.

(Contd. on page 6)



Printing date 25.03.2019 Revision: 25.03.2019

Trade name: STD-NICKEL 5% HNO3 10000 MG/L

		(Contd. of page 5
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.	
Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Water:	94.0 %	
Solids content:	1.0 %	
· 9.2 Other information	No further relevant information available.	

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

# SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity

Suspected of causing cancer.

- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

GB



Printing date 25.03.2019 Revision: 25.03.2019

Trade name: STD-NICKEL 5% HNO3 10000 MG/L

(Contd. of page 6)

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

CECTION	7 1 4	70	, •	c .
<b>SECTION</b>	14:	<i><b>Transport</b></i>	un	formation

· 14.1 UN-Number · ADR, IMDG, IATA	UN3264
· 14.2 UN proper shipping name · ADR	3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
· IMDG, IATA	(Nitric Acid) CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric Acid)

- · 14.3 Transport hazard class(es)
- $\cdot ADR$



Class 8 (C1) Corrosive substances.

(Contd. on page 8)



Printing date 25.03.2019 Revision: 25.03.2019

Trade name: STD-NICKEL 5% HNO3 10000 MG/L

	(Contd. of pag
Label	8
IMDG, IATA	
Class	8 Corrosive substances.
Label	8
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Corrosive substances.
Danger code (Kemler):	80
EMS Number:	F- $A$ , $S$ - $B$
Segregation groups	Acids
Stowage Category	A SINO SIL SIL SIL
Stowage Code	SW2 Clear of living quarters.
14.7 Transport in bulk according to Anna	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
<b></b>	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	<i>E</i>
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANI
•	N.O.S. (NITRIC ACID), 8, III

SECTION 15: Regulatory information				
· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture				
0110. / / 02 10 0	Vater	94.0%		
EINECS: 231-791-2				

GB



Printing date 25.03.2019 Revision: 25.03.2019

Trade name: STD-NICKEL 5% HNO3 10000 MG/L

		(Contd.	of page 8)
CAS: 7697-37-2	Nitric Acid	� Ox. Liq. 2, H272	5.0%
EINECS: 231-714-2		🔖 Skin Corr. 1A, H314	
CAS: 7440-02-0 EINECS: 231-111-4		& Carc. 2, H351; STOT RE 1, H372 Skin Sens. 1, H317	1.0%

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 27
- · National regulations:
- · Information about limitation of use:

Workers are not allowed to be exposed to this hazardous material. Exceptions can be made by the authorities in certain cases.

- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

#### Disclaimer

The information provided in this Material Safety Data Sheet is based on our present knowledge, and believed to be correct at the date of publication. However, no representation is made concerning its accuracy and completeness. It is intended as guidance only, and is not to be considered a warranty or quality specification. All materials may present unknown hazards, and should be used with caution. Although certain hazards are described, we cannot guarantee that these are the only hazards which exist. PerkinElmer Life and Analytical Sciences shall not be held liable for any damage resulting from handling or from contact with the product.

#### · Relevant phrases

H272 May intensify fire; oxidiser.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

#### · Department issuing SDS:

Environmental, Health and Safety

PerkinElmer Chalfont Road Buckinghamshire

Seer Green HP9 2FX United Kingdom

Telephone : 0800-89 60 46 FAX : 0800-89 17 14

· Contact:

Within the USA: 1-(800)-762-4000 Outside the USA: 1-(203)-712-8488

#### · Abbreviations and acronyms

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 10)



Printing date 25.03.2019 Revision: 25.03.2019

Trade name: STD-NICKEL 5% HNO3 10000 MG/L

(Contd. of page 9)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Ox. Liq. 2: Oxidizing liquids – Category 2 Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

\* Data compared to the previous version altered.