

*

*

USA

acc. to OSHA HCS

Printing date 03/25/2019

Review date 03/25/2019

1 Identificatio	on
· Product ident	ifier
· Article numbe	STD-NICKEL 5% HNO3 10000 MG/L er N9304117 f the substance / the mixture Laboratory chemicals
• Details of the • Manufacturer	supplier of the safety data sheet /Supplier:
CustomerCare 203-925-4600 Emergency te	rt Avenue ecticut 06484 USA eUS@perkinelmer.com lephone number:
CHEMTREC	(within US) 800-424-9300 (from outside US) +1 703-527-3887 (call collect) (within AU) +(61)-290372994
e Hazard(s) i	dentification
· Classification	of the substance or mixture
Hec	alth hazard
Carc. 2	H351 Suspected of causing cancer.
	H372 Causes damage to organs through prolonged or repeated exposure.
Cor	rosion
Skin Corr. 1B	H314 Causes severe skin burns and eye damage.
	H318 Causes serious eye damage.
	H317 May cause an allergic skin reaction.
	<i>ments</i> The product is classified and labeled according to the Globally Harmonized System (GHS). <i>rams</i> GHS05, GHS07, GHS08
• Hazard-detern Nitric Acid nickel	nining components of labeling:
· Hazard staten	
	severe skin burns and eye damage. Ise an allergic skin reaction.
	ed of causing cancer.
1	(Contd. on page



Printing date 03/25/2019

Review date 03/25/2019

Trade name: STD-NICKEL 5% HNO3 10000 MG/L

	(Contd. of page 1)
H372 Causes de	amage to organs through prolonged or repeated exposure.
· Precautionary	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dusts or mists.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P	331 If swallowed: Rinse mouth. Do NOT induce vomiting.
P303+P361+P	353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P	338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a poison center/doctor.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P321	Specific treatment (see on this label).
P314	Get medical advice/attention if you feel unwell.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
• Classification s	
· NFPA ratings ((scale 0 - 4)
	Health = 3
F	Fire = 0
3 0 R	Reactivity = 0
• HMIS-ratings ((scale 0 - 4)
HEALTH 3	Health = 3
	Fire = 0
	$\begin{aligned} F tre &= 0 \\ Reactivity &= 0 \end{aligned}$
• Other hazards	
	oes not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or
formaldehydes.	bes not contain any organic natogen compounds (AOA), nitrates, neavy metal compounds of
	and vPvB assessment
• PBT: Not appli	
• vPvB: Not appl	

3 Composition/information on ingredients

• Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)

USA



Printing date 03/25/2019

Review date 03/25/2019

Trade name: STD-NICKEL 5% HNO3 10000 MG/L

		(Contd.	of page 2)
· Hazardous	components:		
7697-37-2	Nitric Acid	Ox. Liq. 2, H272 Skin Corr. 1A, H314	5.0%
7440-02-0	nickel	Carc. 2, H351; STOT RE 1, H372 Skin Sens. 1, H317	1.0%
	Components		
7732-18-5	Water		94.0%

4 First-aid measures

· Description of first aid measures

- · General information:
- Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air and to be sure call for a doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- *Indication of any immediate medical attention and special treatment needed No further relevant information available.*

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

• Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

• Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

(Contd. on page 4)

USA



Printing date 03/25/2019

Review date 03/25/2019

Trade name: STD-NICKEL 5% HNO3 10000 MG/L

See Section See Section See Section	to other sections 7 for information on safe handling. 8 for information on personal protection equipment. 13 for disposal information. Action Criteria for Chemicals	(Contd. of page 3)
· PAC-1:		
7697-37-2	Nitric Acid	0.16 ppm
7440-02-0	nickel	$4.5 mg/m^3$
· PAC-2:		
7697-37-2	Nitric Acid	24 ppm
7440-02-0	nickel	50 mg/m^3
· PAC-3:		
7697-37-2	Nitric Acid	92 ppm
7440-02-0	nickel	99 mg/m ³

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities

· Storage:

- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.

• Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

• Components with limit values that require monitoring at the workplace:

7697-37-2 Nitric Acid

PEL Long-term value: 5 mg/m³, 2 ppm

REL Short-term value: 10 mg/m³, 4 ppm

Long-term value: 5 mg/m³, 2 ppm

TLV Short-term value: 10 mg/m³, 4 ppm Long-term value: 5.2 mg/m³, 2 ppm

(Contd. on page 5)

USA



Printing date 03/25/2019

Review date 03/25/2019

Trade name: STD-NICKEL 5% HNO3 10000 MG/L

(Contd. of page 4) 7440-02-0 nickel *PEL* Long-term value: 1 mg/m^3 *REL* Long-term value: 0.015 mg/m^3 as Ni; See Pocket Guide App. A TLV Long-term value: 1.5* mg/m³ elemental, *inhalable fraction • Additional information: The lists that were valid during the creation were used as basis. · Exposure controls · Personal protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes. Avoid contact with the eyes and skin. · Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. · Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. • Eye protection: Tightly sealed goggles or safety glasses 9 Physical and chemical properties · Information on basic physical and chemical properties · General Information

• Appearance: Form:

Liquid

USA



Printing date 03/25/2019

Review date 03/25/2019

Trade name: STD-NICKEL 5% HNO3 10000 MG/L

		(Contd. of page 3
Color:	Clear	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
	Not determined.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density:	Not determined.	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wate	r): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Water:	94.0 %	
VOC content:	0.00 %	
Solids content:	1.0 %	
Other information	No further relevant information available.	

10 Stability and reactivity

• *Reactivity* No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous reactions No dangerous reactions known.

· Conditions to avoid No further relevant information available.

• *Incompatible materials:* No further relevant information available.

(Contd. on page 7)



Printing date 03/25/2019

Review date 03/25/2019

(Contd. of page 6)

Trade name: STD-NICKEL 5% HNO3 10000 MG/L

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Caustic effect on skin and mucous membranes.
- on the eye:
- Strong caustic effect.
- Strong irritant with the danger of severe eye injury.
- Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

 · IARC (International Agency for Research on Cancer)

 7440-02-0
 nickel
 2B

 · NTP (National Toxicology Program)
 7440-02-0
 nickel
 R

 · OSHA-Ca (Occupational Safety & Health Administration)
 R

 None of the ingredients is listed.
 K

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:

· General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

(Contd. on page 8)



Printing date 03/25/2019

Review date 03/25/2019

Trade name: STD-NICKEL 5% HNO3 10000 MG/L

(Contd. of page 7)

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Dispose of container and materials in accordance with local, regional and national regulations.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

· UN-Number · DOT, ADR, IMDG, IATA	UN3264
· UN proper shipping name	
·DOT	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric Acid)
·ADR	3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (N
	Acid)
· IMDG, IATA	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric Ad
· Transport hazard class(es)	
· DOT, IMDG, IATA	
\land	
· Class · Label	8 Corrosive substances 8
·ADR	
· Class	8 (C1) Corrosive substances
· Label	8
· Packing group	
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Corrosive substances
· Danger code (Kemler):	80
· EMS Number:	F- A , S - B
· Segregation groups	Acids
	1 • 1



*

acc. to OSHA HCS

Printing date 03/25/2019

Review date 03/25/2019

Trade name: STD-NICKEL 5% HNO3 10000 MG/L

	(Contd. of page
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex II oj MARPOL73/78 and the IBC Code	f Not applicable.
Transport/Additional information:	
DOT Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
ADR Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S (NITRIC ACID), 8, III

Safety, hea	lth and environmental regulations/	legislation specific for the substance or mixture	
7732-18-5	Water		94.0%
7697-37-2	Nitric Acid	Ox. Liq. 2, H272 Skin Corr. 1A, H314	5.0%
7440-02-0	nickel	Carc. 2, H351; STOT RE 1, H372 Skin Sens. 1, H317	1.0%
Sara			
Section 35	5 (extremely hazardous substances)	:	
7697-37-2	Nitric Acid		
Section 31	3 (Specific toxic chemical listings):		
7697-37-2	Nitric Acid		
7440-02-0	nickel		
	xic Substances Control Act): ents are listed.		
7697-37-2	Nitric Acid		
7440-02-0	nickel		
7732-18-5	Water		
Proposition	n 65		
Chemicals	known to cause cancer:		
	nickel		



Printing date 03/25/2019

Review date 03/25/2019

Trade name: STD-NICKEL 5% HNO3 10000 MG/L

(Contd. of page 9)

A5

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

• Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

TLV (Threshold Limit Value established by ACGIH)

7440-02-0 nickel

·NIOSH-Ca (National Institute for Occupational Safety and Health)

7440-02-0 nickel

· National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to this hazardous material. Exceptions can be made by the authorities in certain cases.

• Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Disclaimer

The information provided in this Material Safety Data Sheet is based on our present knowledge, and believed to be correct at the date of publication. However, no representation is made concerning its accuracy and completeness. It is intended as guidance only, and is not to be considered a warranty or quality specification. All materials may present unknown hazards, and should be used with caution. Although certain hazards are described, we cannot guarantee that these are the only hazards which exist. PerkinElmer shall not be held liable for any damage resulting from handling or from contact with the product.

• **Department issuing SDS:** Environmental, Health and Safety

· Contact:

Within the USA: 1-(800)-762-4000 Outside the USA: 1-(203)-712-8488

• Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 11)



Printing date 03/25/2019

Review date 03/25/2019

Trade name: STD-NICKEL 5% HNO3 10000 MG/L

(Contd. of page 10)

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Ox. Liq. 2: Oxidizing liquids – Category 2 Skin Corr. 1A: Skin corrosion/irritation - Category 1A Skin Corr. 1B: Skin corrosion/irritation – Category 1B Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Skin Sens. 1: Skin sensitisation – Category 1 Carc. 2: Carcinogenicity – Category 2STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1 • * Data compared to the previous version altered.