

Printing date 27.07.2021 Revision: 27.07.2021

Hazardous according to criteria of Australian Safety and Compensation Council.

1 Identification

- · Product identifier
- · Trade name: STD MES110901A MULTI-ELEMENT- 125mL
- · Article number: N9308544
- · Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Laboratory chemicals
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

PerkinElmer, Inc. 710 Bridgeport Avenue Shelton, Connecticut 06484 USA CustomerCareUS@perkinelmer.com 203-925-4600

Supplier/Local:

PerkinElmer Australia Lvl 2, Bldg 5, Brandon Office Park

530-540 Springvale Road

Glen Waverley

Melbourne

VIC 3150

Australia

1-800-033-391

ausales@perkinelmer.com

· Emergency telephone number:

CHEMTREC (within US) 800-424-9300

CHEMTREC (from outside US) +1 703-527-3887 (call collect)

CHEMTREC (within AU) +(61)-290372994

2 Hazard(s) Identification

Classification of the substance or mixture



Skin Corr. 1 H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- · Label elements
- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms GHS05
- · Signal word Danger

(Contd. on page 2)



Printing date 27.07.2021 Revision: 27.07.2021

Trade name: STD MES110901A MULTI-ELEMENT- 125mL

(Contd. of page 1)

· Hazard-determining components of labelling:

Nitric Acid

· Hazard statements

H314 Causes severe skin burns and eye damage.

· Precautionary statements

P260 Do not breathe dusts or mists.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Other hazards

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.

- Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

7697-37-2	Nitric Acid	© Ox. Liq. 2, H272 Skin Corr. 1, H314	10.0%
· Additional	Components		
7732-18-5	Water		89.96%
7429-91-6	dysprosium		0.001%
7439-91-0	lanthanum		0.001%
7439-92-1	lead & Repr. 1A, H360		0.001%
7439-93-2	lithium Water-react. 1, H260 Skin Corr. 1, H314		0.001%
7439-94-3	LUTETIUM		0.001%
7439-96-5	manganese		0.001%
7440-00-8	neodymium		0.001%
7440-02-0	nickel Carc. 2, H351; STOT RE 1, H372 Skin Sens. 1, H317		0.001%

AU



Printing date 27.07.2021 Revision: 27.07.2021

Trade name: STD MES110901A MULTI-ELEMENT- 125mL

7440 10 0	Duggoodynging	(Contd. of pag
	Praseodymium	0.001
7440-17-7	water-react. 1, H260 Water-react. 1, H260 Skin Corr. 1, H314; Eye Dam. 1, H318	0.001
7440-19-9	samarium	0.001
7440-20-2	Scandium from Sacndium Oxide	0.001
7440-24-6	strontium Water-react. 1, H260	0.001
7440-27-9	terbium	0.001
7440-28-0	thallium Acute Tox. 2, H300; Acute Tox. 2, H330 STOT RE 2, H373	0.001
7440-29-1	thorium	0.001
7440-30-4	THULIUM	0.001
7440-38-2	Arsenic Arsenic Arsenic Arsenic	0.001
7440-39-3	barium Water-react. 2, H261	0.001
7440-41-7	beryllium Acute Tox. 3, H301; Acute Tox. 2, H330 Carc. 1B, H350; STOT RE 1, H372 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	0.001
7440-43-9	cadmium Acute Tox. 3, H301; Acute Tox. 2, H330 Muta. 2, H341; Carc. 1B, H350; Repr. 2, H361; STOT RE 1, H372	0.001
7440-45-1	cerium • Water-react. 2, H261	0.00
7440-46-2	· · · · · · · · · · · · · · · · · · ·	0.00
7440-47-3	chromium	0.00
7440-48-4	cobalt Resp. Sens. 1, H334 Skin Sens. 1, H317	0.00
7440-50-8	•	0.00
7440-52-0		0.00
7440-53-1		0.00
7440-54-2	-	0.00
7440-55-3		0.00
7440-60-0	holmium	0.00
7440-61-1	<i>uranium Acute Tox. 2, H300; Acute Tox. 2, H330 STOT RE 2, H373</i>	0.00



Printing date 27.07.2021 Revision: 27.07.2021

Trade name: STD MES110901A MULTI-ELEMENT- 125mL

		(Contd. of page 3)
7440-62-2	vanadium	0.001%
7440-64-4	ytterbium	0.001%
7440-65-5	yttrium	0.001%
7440-66-6	zinc Pyr. Sol. 1, H250; Water-react. 1, H260	0.001%
7440-69-9	bismuth	0.001%
7440-70-2	calcium Water-react. 2, H261	0.001%
7440-74-6	Indium	0.001%
7782-49-2	selenium	0.001%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose contaminated material as waste according to item 13.

(Contd. on page 5)



Printing date 27.07.2021 Revision: 27.07.2021

Trade name: STD MES110901A MULTI-ELEMENT- 125mL

(Contd. of page 4)

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

- · Handling:
- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about fire and explosion protection: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage.
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

7697-37-2 Nitric Acid

WES Short-term value: 10 mg/m³, 4 ppm Long-term value: 5.2 mg/m³, 2 ppm

- Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



(Contd. on page 6)



Printing date 27.07.2021 Revision: 27.07.2021

Trade name: STD MES110901A MULTI-ELEMENT- 125mL

(Contd. of page 5)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Information on basic physical and chemi	ical properties
General Information	icui proportios
Appearance:	
	Fluid
Colour:	Dark brown
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.
Flash point:	Not applicable.
Flammability (solid, gas):	Not applicable.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
• •	Not determined.
Explosion limits:	
	Not determined.
Upper:	Not determined.
Vapour pressure at 20 °C:	23 hPa
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.

(Contd. on page 7)



Printing date 27.07.2021 Revision: 27.07.2021

Trade name: STD MES110901A MULTI-ELEMENT- 125mL

		(Contd. of page 6
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.	
Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Water:	90.0 %	
· Other information	No further relevant information available.	

10 Stability and Reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity
- · Primary irritant effect:
- · Skin corrosion/irritation Strong caustic effect on skin and mucous membranes.
- · Serious eye damage/irritation

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- Respiratory or skin sensitisation No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

12 Ecological Information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.

(Contd. on page 8)



Printing date 27.07.2021 Revision: 27.07.2021

Trade name: STD MES110901A MULTI-ELEMENT- 125mL

(Contd. of page 7)

- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

7 1	/III			
14	Tranc	nort	into	rmation
	I I WILD	$\boldsymbol{\nu}\boldsymbol{\sigma}\boldsymbol{\iota}\boldsymbol{\iota}$	יטוטוט	

· UN-Number · ADG, IMDG, IATA	UN2031
· UN proper shipping name	
$\cdot ADG$	2031 NITRIC ACID
	3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
	(NITRIC ACID)
· IMDG, IATA	NITRIC ACID
T (1 1 1 ()	

- · Transport hazard class(es)
- $\cdot ADG$



• Class 8 (C1) Corrosive substances. • Label 8

· IMDG, IATA



· Class 8 Corrosive substances.

(Contd. on page 9)



Printing date 27.07.2021 Revision: 27.07.2021

Trade name: STD MES110901A MULTI-ELEMENT- 125mL

	(Contd. of p
Label	8
Packing group	
ADG, IMDG, IATA	II
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Corrosive substances.
Hazard identification number (Kemler code):	80
EMS Number:	F- A , S - B
Segregation groups	Strong acids
Stowage Category	D
Segregation Code	SG36 Stow "separated from" SGG18-alkalis.
	SG49 Stow "separated from" SGG6-cyanides
Transport in bulk according to Annex II of Mar	nol
and the IBC Code	Not applicable.
Transport/Additional information:	
ADG	
Limited quantities (LQ)	1L
Excepted quantities (\widetilde{EQ})	Code: E2
• • • • • •	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	E
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
	UN 2031 NITRIC ACID, 8, II

Safety, health and environmental regulations/legislation specific for the substance or mixture			
7732-18-5	Water		89.96%
7697-37-2	Nitric Acid	© Ox. Liq. 2, H272 Skin Corr. 1, H314	10.0%
7429-91-6	dysprosium		0.001%
Australia:	Priority Existing Chemicals		

- · Directive 2012/18/EU
- $\cdot \textit{Named dangerous substances-ANNEX I} \ \textit{None of the ingredients is listed}.$

(Contd. on page 10)



Printing date 27.07.2021 Revision: 27.07.2021

Trade name: STD MES110901A MULTI-ELEMENT- 125mL

(Contd. of page 9)

- · National regulations:
- · Information about limitation of use:

Workers are not allowed to be exposed to this hazardous material. Exceptions can be made by the authorities in certain cases.

- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Disclaimer

The information provided in this Material Safety Data Sheet is based on our present knowledge, and believed to be correct at the date of publication. However, no representation is made concerning its accuracy and completeness. It is intended as guidance only, and is not to be considered a warranty or quality specification. All materials may present unknown hazards, and should be used with caution. Although certain hazards are described, we cannot guarantee that these are the only hazards which exist. PerkinElmer Life and Analytical Sciences shall not be held liable for any damage resulting from handling or from contact with the product.

· Relevant phrases

H250 Catches fire spontaneously if exposed to air.

H260 In contact with water releases flammable gases which may ignite spontaneously.

H261 In contact with water releases flammable gases.

H272 May intensify fire; oxidiser.

H300 Fatal if swallowed.

H301 Toxic if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H331 Toxic if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

H351 Suspected of causing cancer.

H360 May damage fertility or the unborn child.

H361 Suspected of damaging fertility or the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure.

- · Department issuing SDS: Environmental, Health and Safety
- · Contact:

Within the USA: 1-(800)-762-4000 Outside the USA: 1-(203)-712-8488

· Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 11)



Printing date 27.07.2021 Revision: 27.07.2021

Trade name: STD MES110901A MULTI-ELEMENT- 125mL

(Contd. of page 10)

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Ox. Liq. 2: Oxidizing liquids – Category 2 Skin Corr. 1: Skin corrosion/irritation – Category 1 Eye Dam. 1: Serious eye damage/eye irritation – Category 1

* Data compared to the previous version altered.